SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom II X4 940)

SPECint®_rate2006 = 53.5

SPECint_rate_base2006 = 51.9

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2009
Hardware Availability: Jan-2009
Software Availability: Nov-2008



Hardware

CPU Name:	AMD Phenom II X4 940
CPU Characteristics:	
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	6 MB I+D on chip per chip
Other Cache:	None
Memory:	4 GB (4x1GB DDR2-800 CL5)
Disk Subsystem:	Seagate 320 GB SATA, 7200RPM
Other Hardware:	None

Software

Operating System:	Windows Vista Ultimate w/ SP1 (64-bit)
Compiler:	Intel C++ Compiler Professional 11.0 for IA32 Build 20080930 Package ID: w_cproc_p_11.0.054 Microsoft Visual Studio 2008 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	SmartHeap Library Version 8.1 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.
(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom II X4 940)

SPECint_rate2006 = 53.5

SPECint_rate_base2006 = 51.9

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2009
Hardware Availability: Jan-2009
Software Availability: Nov-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	594	66.0	**594**	**66.0**	596	65.6	4	**463**	**84.4**	462	84.8	464	84.4
401.bzip2	4	886	43.6	867	44.4	**875**	**44.0**	4	867	44.4	**874**	**44.0**	879	44.0
403.gcc	4	638	50.4	645	50.0	**642**	**50.0**	4	**627**	**51.2**	622	51.6	627	51.2
429.mcf	4	1000	36.4	1001	36.4	**1000**	**36.4**	4	1000	36.4	**1000**	**36.4**	1001	36.4
445.gobmk	4	542	77.2	542	77.6	**542**	**77.6**	4	507	82.8	**507**	**82.8**	507	82.8
456.hmmer	4	**1570**	**23.6**	1575	23.6	1569	23.6	4	1563	24.0	1570	23.6	**1569**	**23.6**
458.sjeng	4	774	62.4	**774**	**62.4**	775	62.4	4	**714**	**67.6**	714	67.6	714	67.6
462.libquantum	4	**1124**	**73.6**	1123	73.6	1124	73.6	1	363	57.1	**363**	**57.1**	363	57.1
464.h264ref	4	849	104	**849**	**104**	848	104	4	786	113	787	112	**787**	**112**
471.omnetpp	4	714	34.8	**714**	**34.8**	714	35.2	4	**665**	**37.6**	665	37.6	666	37.6
473.astar	4	677	41.6	**677**	**41.6**	677	41.6	4	652	43.2	651	43.2	**651**	**43.2**
483.xalancbmk	4	**481**	**57.2**	484	57.2	479	57.6	4	**481**	**57.2**	484	57.2	479	57.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Binaries were built on Windows Vista Ultimate (32-bit)
OMP_NUM_THREADS set to number of logical processors as seen by the OS
KMP_AFFINITY set to physical,0
submit disabled for 462.libquantum peak
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qc99
```

C++ benchmarks:

```
icl -Qvc9
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Continued on next page

Base Portability Flags (Continued)

483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:
`/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000`

C++ benchmarks:
`/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
`icl -Qvc9 -Qc99`

C++ benchmarks:
`icl -Qvc9`

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Peak Optimization Flags

C benchmarks:

400.perlbench: `/arch:SSE2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Continued on next page

Peak Optimization Flags (Continued)

401.bzip2: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias /F512000000

403.gcc: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

429.mcf: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

445.gobmk: /arch:SSE2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmer: /arch:SSE2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias /F512000000

458.sjeng: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 /F512000000

462.libquantum: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qpar-runtime-control -Qvec-guard-write /F512000000

464.h264ref: Same as 456.hmmer

C++ benchmarks:

471.omnetpp: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

473.astar: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=routine /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 01:00:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 June 2009.