



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9950)

SPECfp®\_rate2006 = 37.8

SPECfp\_rate\_base2006 = 36.9

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Jul-2008

Software Availability: Nov-2008



### Hardware

CPU Name: AMD Phenom X4 9950  
 CPU Characteristics:  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 512 KB I+D on chip per core

Continued on next page

### Software

Operating System: Windows Vista Ultimate w/ SP1 (64-bit)  
 Compiler: Intel C++ Compiler Professional 11.0 for IA32  
 Build 20080930 Package ID: w\_cproc\_p\_11.0.054  
 Intel Visual Fortran Compiler Professional 11.0 for IA32  
 Build 20080930 Package ID: w\_cprof\_p\_11.0.054  
 Microsoft Visual Studio 2008 (for libraries)  
 Auto Parallel: No  
 File System: NTFS

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9950)

SPECfp\_rate2006 = 37.8

SPECfp\_rate\_base2006 = 36.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Jul-2008

Software Availability: Nov-2008

L3 Cache: 2 MB I+D on chip per chip  
Other Cache: None  
Memory: 4 GB (4x1GB DDR2-800 CL5)  
Disk Subsystem: Seagate 320 GB SATA, 7200RPM  
Other Hardware: None

System State: Default  
Base Pointers: 32-bit  
Peak Pointers: 32-bit  
Other Software: SmartHeap Library Version 8.1 from <http://www.microquill.com/>

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1442	37.6	<b>1443</b>	<b>37.6</b>	1444	37.6	4	1443	37.6	<b>1443</b>	<b>37.6</b>	1442	37.6
416.gamess	4	1266	62.0	1264	62.0	<b>1265</b>	<b>62.0</b>	4	1263	62.0	<b>1262</b>	<b>62.0</b>	1261	62.0
433.milc	4	<b>1524</b>	<b>24.0</b>	1523	24.0	1525	24.0	4	1521	24.0	<b>1521</b>	<b>24.0</b>	1524	24.0
434.zeusmp	4	<b>821</b>	<b>44.4</b>	827	44.0	821	44.4	4	<b>813</b>	<b>44.8</b>	816	44.8	812	44.8
435.gromacs	4	<b>574</b>	<b>49.6</b>	573	50.0	575	49.6	4	<b>563</b>	<b>50.8</b>	563	50.8	563	50.8
436.cactusADM	4	<b>1013</b>	<b>47.2</b>	1013	47.2	1011	47.2	4	<b>1013</b>	<b>47.2</b>	1013	47.2	1011	47.2
437.leslie3d	4	1525	24.8	<b>1525</b>	<b>24.8</b>	1525	24.8	4	1525	24.8	<b>1524</b>	<b>24.8</b>	1524	24.8
444.namd	4	645	49.6	<b>645</b>	<b>49.6</b>	645	49.6	4	<b>633</b>	<b>50.8</b>	633	50.8	632	50.8
447.dealII	4	944	48.4	938	48.8	<b>940</b>	<b>48.8</b>	4	825	55.6	<b>823</b>	<b>55.6</b>	821	55.6
450.soplex	4	1175	28.4	<b>1174</b>	<b>28.4</b>	1174	28.4	4	1174	28.4	<b>1174</b>	<b>28.4</b>	1175	28.4
453.povray	4	275	77.2	279	76.4	<b>278</b>	<b>76.8</b>	4	<b>232</b>	<b>91.6</b>	232	92.0	232	91.6
454.calculix	4	<b>1767</b>	<b>18.8</b>	1766	18.8	1767	18.8	4	<b>1767</b>	<b>18.8</b>	1768	18.8	1767	18.8
459.GemsFDTD	4	2028	20.8	<b>2029</b>	<b>20.8</b>	2030	20.8	4	2032	20.8	2026	20.8	<b>2031</b>	<b>20.8</b>
465.tonto	4	1154	34.0	<b>1148</b>	<b>34.4</b>	1144	34.4	4	1105	35.6	1106	35.6	<b>1106</b>	<b>35.6</b>
470.lbm	4	<b>2283</b>	<b>24.0</b>	2283	24.0	2283	24.0	4	2282	24.0	<b>2282</b>	<b>24.0</b>	2282	24.0
481.wrf	4	1006	44.4	1010	44.4	<b>1010</b>	<b>44.4</b>	4	1006	44.4	1010	44.4	<b>1010</b>	<b>44.4</b>
482.sphinx3	4	1904	40.8	<b>1904</b>	<b>40.8</b>	1905	40.8	4	1907	40.8	1904	40.8	<b>1905</b>	<b>40.8</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## General Notes

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply  
Binaries were built on Windows Vista Ultimate (32-bit)

## Base Compiler Invocation

C benchmarks:  
icl -Qvc9 -Qc99

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9950)

SPECfp\_rate2006 = 37.8

SPECfp\_rate\_base2006 = 36.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Jul-2008

Software Availability: Nov-2008

## Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qc99 ifort

## Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
453.povray: -DSPEC\_CPU\_WINDOWS\_ICL  
454.calculix: -DSPEC\_CPU\_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC\_CPU\_WINDOWS\_ICL

## Base Optimization Flags

C benchmarks:

/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

C++ benchmarks:

/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
/F1000000000 shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

Benchmarks using both Fortran and C:

/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

## Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qc99

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**GIGA-BYTE Technology Co. Ltd.**

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9950)

**SPECfp\_rate2006 = 37.8**

**SPECfp\_rate\_base2006 = 36.9**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Jan-2009

**Hardware Availability:** Jul-2008

**Software Availability:** Nov-2008

## Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

icl -Qvc9 -Qc99 ifort

## Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
453.povray: -DSPEC\_CPU\_WINDOWS\_ICL  
454.calculix: -DSPEC\_CPU\_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC\_CPU\_WINDOWS\_ICL

## Peak Optimization Flags

C benchmarks:

433.milc: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Oa /F1000000000

470.lbm: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch  
/F1000000000

482.sphinx3: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qunroll2 /F1000000000

C++ benchmarks:

444.namd: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlw32m.lib  
-link /FORCE:MULTIPLE

447.dealII: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias  
-Qscalar-rep- /F1000000000 shlw32m.lib  
-link /FORCE:MULTIPLE

450.soplex: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- /F1000000000 shlw32m.lib  
-link /FORCE:MULTIPLE

453.povray: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000  
shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom X4 9950)

SPECfp\_rate2006 = 37.8

SPECfp\_rate\_base2006 = 36.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jan-2009

Hardware Availability: Jul-2008

Software Availability: Nov-2008

## Peak Optimization Flags (Continued)

410.bwaves: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

416.gamess: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F1000000000

434.zeusmp: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- /F1000000000

437.leslie3d: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

459.GemsFDTD: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qopt-prefetch /F1000000000

465.tonto: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000

Benchmarks using both Fortran and C:

435.gromacs: /arch:SSE2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

436.cactusADM: basepeak = yes

454.calculix: /arch:SSE2 -Qipo -O3 -Qprec-div- /F1000000000

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 01:05:50 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 23 June 2009.