



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

**SPECfp®2006 = 21.6**

Gateway GW2000h-GW170h F1 (Intel Xeon E5502)

**SPECfp\_base2006 = 20.7**

CPU2006 license: 97


Test date: Dec-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009



### Hardware

CPU Name: Intel Xeon E5502  
 CPU Characteristics:  
 CPU MHz: 1867  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64)  
 Kernel 2.6.27.19-5  
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux  
 Build 20090131 Package ID: I\_cprof\_p\_11.0.080,  
 I\_cprof\_p\_11.0.080  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

SPECfp2006 = **21.6**

Gateway GW2000h-GW170h F1 (Intel Xeon E5502)

SPECfp\_base2006 = **20.7**

CPU2006 license: 97

Test date: Dec-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

L3 Cache: 4 MB I+D on chip per chip  
Other Cache: None  
Memory: 24 GB (12 x 2 GB DDR3-1066 RDIMM, running at 800 MHz)  
Disk Subsystem: 1 x 500 GB SATA II, 7200 RPM  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<b>229</b>	<b>59.4</b>	232	58.5	229	59.4	229	59.4	232	58.5	<b>232</b>	<b>58.6</b>
416.gamess	1370	14.3	1368	14.3	<b>1369</b>	<b>14.3</b>	<b>1275</b>	<b>15.4</b>	1274	15.4	1276	15.3
433.milc	392	23.4	<b>392</b>	<b>23.4</b>	392	23.4	394	23.3	<b>394</b>	<b>23.3</b>	396	23.2
434.zeusmp	542	16.8	<b>543</b>	<b>16.8</b>	543	16.8	542	16.8	<b>543</b>	<b>16.8</b>	543	16.8
435.gromacs	535	13.4	<b>533</b>	<b>13.4</b>	533	13.4	<b>524</b>	<b>13.6</b>	524	13.6	526	13.6
436.cactusADM	394	30.3	392	30.5	<b>393</b>	<b>30.4</b>	366	32.6	<b>367</b>	<b>32.6</b>	369	32.4
437.leslie3d	<b>516</b>	<b>18.2</b>	518	18.2	482	19.5	<b>516</b>	<b>18.2</b>	518	18.2	482	19.5
444.namd	719	11.2	<b>719</b>	<b>11.2</b>	719	11.2	<b>726</b>	<b>11.0</b>	726	11.0	726	11.1
447.dealII	573	20.0	<b>573</b>	<b>20.0</b>	573	20.0	538	21.3	538	21.2	<b>538</b>	<b>21.3</b>
450.soplex	<b>474</b>	<b>17.6</b>	474	17.6	475	17.6	468	17.8	470	17.8	<b>469</b>	<b>17.8</b>
453.povray	325	16.4	<b>324</b>	<b>16.4</b>	324	16.4	250	21.3	<b>251</b>	<b>21.2</b>	252	21.1
454.calculix	507	16.3	<b>507</b>	<b>16.3</b>	506	16.3	487	17.0	<b>486</b>	<b>17.0</b>	486	17.0
459.GemsFDTD	361	29.4	352	30.2	<b>352</b>	<b>30.1</b>	<b>304</b>	<b>34.9</b>	304	34.9	304	35.0
465.tonto	660	14.9	<b>660</b>	<b>14.9</b>	661	14.9	<b>576</b>	<b>17.1</b>	576	17.1	581	16.9
470.lbm	343	40.0	<b>342</b>	<b>40.2</b>	339	40.6	343	40.0	<b>342</b>	<b>40.2</b>	339	40.6
481.wrf	469	23.8	468	23.9	<b>468</b>	<b>23.8</b>	<b>468</b>	<b>23.9</b>	467	23.9	469	23.8
482.sphinx3	948	20.6	<b>954</b>	<b>20.4</b>	1157	16.8	946	20.6	<b>947</b>	<b>20.6</b>	949	20.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was set for stacksize unlimited

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter  
KMP\_STACKSIZE set to 200M

This result was measured on the Gateway GW2000h-GW170h F1.  
The Acer AW2000h-AW170h F1 and Gateway GW2000h-GW170h F1 are electronically equivalent.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECfp2006 = 21.6**

Gateway GW2000h-GW170h F1 (Intel Xeon E5502)

**SPECfp\_base2006 = 20.7**

**CPU2006 license:** 97

**Test date:** Dec-2009

**Test sponsor:** Acer Incorporated

**Hardware Availability:** Jan-2010

**Tested by:** Acer Incorporated

**Software Availability:** Feb-2009

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECfp2006 = 21.6**

Gateway GW2000h-GW170h F1 (Intel Xeon E5502)

**SPECfp\_base2006 = 20.7**

**CPU2006 license:** 97

**Test date:** Dec-2009

**Test sponsor:** Acer Incorporated

**Hardware Availability:** Jan-2010

**Tested by:** Acer Incorporated

**Software Availability:** Feb-2009

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc

450.soplex: icpc -m32

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
 -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
 -fno-alias

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECfp2006 = 21.6**

Gateway GW2000h-GW170h F1 (Intel Xeon E5502)

**SPECfp\_base2006 = 20.7**

**CPU2006 license:** 97

**Test date:** Dec-2009

**Test sponsor:** Acer Incorporated

**Hardware Availability:** Jan-2010

**Tested by:** Acer Incorporated

**Software Availability:** Feb-2009

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealIII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep- -opt-prefetch

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -opt-prefetch -parallel -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECfp2006 = 21.6**

Gateway GW2000h-GW170h F1 (Intel Xeon E5502)

**SPECfp\_base2006 = 20.7**

**CPU2006 license:** 97

**Test date:** Dec-2009

**Test sponsor:** Acer Incorporated

**Hardware Availability:** Jan-2010

**Tested by:** Acer Incorporated

**Software Availability:** Feb-2009

## Peak Optimization Flags (Continued)

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch  
-parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revH.20100216.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revH.20100216.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 06:29:53 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 16 February 2010.