



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

**SPECint®2006 = 19.3**

Acer AW2000h-AW170h F1 (Intel Xeon E5502)

**SPECint\_base2006 = 17.2**

CPU2006 license: 97


Test date: Nov-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009



### Hardware

CPU Name: Intel Xeon E5502  
 CPU Characteristics:  
 CPU MHz: 1867  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 4 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 24 GB (12 x 2 GB DDR3-1066 RDIMM, running at 800 MHz)  
 Disk Subsystem: 1 x 500 GB SATA II, 7200 RPM  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64)  
 Kernel 2.6.27.19-5  
 Compiler: Intel C++ Compiler 11.0 for Linux  
 Build 20090131 Package ID: I\_cproc\_p\_11.0.080, I\_cprof\_p\_11.0.080  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V8.1  
 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 19.3

Acer AW2000h-AW170h F1 (Intel Xeon E5502)

SPECint\_base2006 = 17.2

CPU2006 license: 97

Test date: Nov-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	730	13.4	<b><u>728</u></b>	<b><u>13.4</u></b>	728	13.4	585	16.7	586	16.7	<b><u>585</u></b>	<b><u>16.7</u></b>
401.bzip2	983	9.81	986	9.79	<b><u>984</u></b>	<b><u>9.81</u></b>	877	11.0	888	10.9	<b><u>883</u></b>	<b><u>10.9</u></b>
403.gcc	519	15.5	<b><u>519</u></b>	<b><u>15.5</u></b>	519	15.5	471	17.1	472	17.1	<b><u>472</u></b>	<b><u>17.1</u></b>
429.mcf	351	26.0	<b><u>344</u></b>	<b><u>26.5</u></b>	343	26.6	337	27.1	<b><u>337</u></b>	<b><u>27.1</u></b>	336	27.1
445.gobmk	<b><u>814</u></b>	<b><u>12.9</u></b>	814	12.9	814	12.9	707	14.8	713	14.7	<b><u>710</u></b>	<b><u>14.8</u></b>
456.hammer	725	12.9	724	12.9	<b><u>724</u></b>	<b><u>12.9</u></b>	520	17.9	520	18.0	<b><u>520</u></b>	<b><u>17.9</u></b>
458.sjeng	868	13.9	872	13.9	<b><u>870</u></b>	<b><u>13.9</u></b>	789	15.3	790	15.3	<b><u>790</u></b>	<b><u>15.3</u></b>
462.libquantum	212	97.9	211	98.2	<b><u>212</u></b>	<b><u>97.9</u></b>	212	97.9	211	98.2	<b><u>212</u></b>	<b><u>97.9</u></b>
464.h264ref	<b><u>1061</u></b>	<b><u>20.9</u></b>	1060	20.9	1062	20.8	962	23.0	<b><u>964</u></b>	<b><u>23.0</u></b>	966	22.9
471.omnetpp	<b><u>453</u></b>	<b><u>13.8</u></b>	453	13.8	452	13.8	400	15.6	<b><u>399</u></b>	<b><u>15.7</u></b>	399	15.7
473.astar	709	9.90	<b><u>710</u></b>	<b><u>9.89</u></b>	711	9.88	619	11.3	622	11.3	<b><u>619</u></b>	<b><u>11.3</u></b>
483.xalancbmk	358	19.3	348	19.8	<b><u>356</u></b>	<b><u>19.4</u></b>	358	19.3	348	19.8	<b><u>356</u></b>	<b><u>19.4</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was set for stacksize unlimited

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter

This result was measured on the Gateway GW2000h-GW170h F1.  
The Acer AW2000h-AW170h F1 and Gateway GW2000h-GW170h F1 are electronically equivalent.

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 19.3

Acer AW2000h-AW170h F1 (Intel Xeon E5502)

SPECint\_base2006 = 17.2

CPU2006 license: 97

Test date: Nov-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Base Portability Flags (Continued)

483.xalanbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel  
-par-runtime-control -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/080/bin/intel64/icc

456.hmmer: /opt/intel/Compiler/11.0/080/bin/intel64/icc

458.sjeng: /opt/intel/Compiler/11.0/080/bin/intel64/icc

C++ benchmarks (except as noted below):

icpc

473.astar: /opt/intel/Compiler/11.0/080/bin/intel64/icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 19.3

Acer AW2000h-AW170h F1 (Intel Xeon E5502)

SPECint\_base2006 = 17.2

CPU2006 license: 97

Test date: Nov-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Peak Portability Flags (Continued)

473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc  
-opt-malloc-options=3

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2  
-ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2  
-ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=routine -auto-ilp32  
-Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 19.3

Acer AW2000h-AW170h F1 (Intel Xeon E5502)

SPECint\_base2006 = 17.2

CPU2006 license: 97

Test date: Nov-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Peak Optimization Flags (Continued)

483.xalanbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revH.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revH.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 06:25:20 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 16 February 2010.