



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 Server Module (Intel Xeon X5690 3.47 GHz)

SPECfp[®]2006 = 64.0

SPECfp_base2006 = 58.6

CPU2006 license: 6


Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Jan-2011

Hardware Availability: Mar-2011

Software Availability: Nov-2010



Hardware

CPU Name: Intel Xeon X5690
 CPU Characteristics: Intel Turbo Boost Technology up to 3.73 GHz
 CPU MHz: 3467
 FPU: Integrated
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Oracle Solaris 10 9/10
 Compiler: Oracle Solaris Studio 12.2
 Auto Parallel: Yes
 File System: ufs
 System State: Default
 Base Pointers: 64-bit
 Peak Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 Server Module (Intel Xeon X5690 3.47 GHz)

SPECfp2006 = **64.0**

SPECfp_base2006 = **58.6**

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Jan-2011

Hardware Availability: Mar-2011

Software Availability: Nov-2010

L3 Cache: 12 MB I+D on chip per chip
Other Cache: None
Memory: 48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC)
Disk Subsystem: 1 x 300 GB 10000 RPM SAS2
Other Hardware: None

Other Software: Microquill SmartHeap V9.01
Apache C++ Standard Library V4.2.1

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	75.2	181	75.1	181	<u>75.1</u>	<u>181</u>	75.2	181	75.1	181	<u>75.1</u>	<u>181</u>
416.gamess	<u>757</u>	<u>25.9</u>	757	25.9	758	25.8	687	28.5	<u>687</u>	<u>28.5</u>	686	28.5
433.milc	<u>198</u>	<u>46.3</u>	170	53.9	199	46.2	<u>172</u>	<u>53.5</u>	171	53.6	201	45.7
434.zeusmp	<u>121</u>	<u>75.2</u>	122	74.4	121	75.3	<u>110</u>	<u>82.5</u>	110	82.5	111	82.3
435.gromacs	173	41.2	<u>173</u>	<u>41.2</u>	173	41.2	163	43.8	<u>163</u>	<u>43.9</u>	162	44.0
436.cactusADM	66.5	180	66.7	179	<u>66.6</u>	<u>179</u>	45.4	263	46.1	259	<u>45.6</u>	<u>262</u>
437.leslie3d	85.6	110	85.5	110	<u>85.6</u>	<u>110</u>	85.6	110	85.5	110	<u>85.6</u>	<u>110</u>
444.namd	<u>402</u>	<u>20.0</u>	402	20.0	402	19.9	<u>402</u>	<u>20.0</u>	402	20.0	402	19.9
447.dealII	<u>233</u>	<u>49.1</u>	233	49.1	233	49.0	231	49.5	230	49.8	<u>230</u>	<u>49.7</u>
450.soplex	225	37.1	<u>225</u>	<u>37.0</u>	225	37.0	210	39.7	<u>210</u>	<u>39.7</u>	210	39.7
453.povray	171	31.2	<u>171</u>	<u>31.1</u>	171	31.1	135	39.5	134	39.6	<u>135</u>	<u>39.5</u>
454.calculix	<u>239</u>	<u>34.6</u>	239	34.6	239	34.6	223	37.0	<u>223</u>	<u>37.0</u>	223	37.0
459.GemsFDTD	<u>99.6</u>	<u>107</u>	99.6	107	99.5	107	98.9	107	98.2	108	<u>98.5</u>	<u>108</u>
465.tonto	261	37.7	272	36.1	<u>262</u>	<u>37.6</u>	223	44.1	<u>223</u>	<u>44.1</u>	223	44.1
470.lbm	105	131	105	131	<u>105</u>	<u>131</u>	103	134	102	134	<u>103</u>	<u>134</u>
481.wrf	173	64.7	168	66.4	<u>168</u>	<u>66.3</u>	155	71.8	<u>155</u>	<u>71.8</u>	155	71.9
482.sphinx3	313	62.2	<u>313</u>	<u>62.3</u>	313	62.3	<u>292</u>	<u>66.7</u>	290	67.1	292	66.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

The Apache C++ Standard Library V4.2.1 was installed from <http://stdcxx.apache.org/download.html> using:
alias gmake=specmake
gmake BUILDTYPE=8D CONFIG=sunpro.config

Operating System Notes

```
ulimit -s unlimited (shell)

/etc/system parameters
tune_t_fsflushr=10
autoup=900
lpg_alloc_prefer=1
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 Server Module (Intel Xeon X5690 3.47 GHz)

SPECfp2006 = 64.0

SPECfp_base2006 = 58.6

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Jan-2011

Hardware Availability: Mar-2011

Software Availability: Nov-2010

Platform Notes

Load Default BIOS Settings and then change the following
Hardware Prefetch Enabled
Adjacent Cache Line Prefetch Enabled
L1 Data Prefetch Enabled

General Notes

Environment variables set by runspec before the start of the run:

OMP_NUM_THREADS = "12"

SUNW_MP_PROCBIND = "23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0"

SUNW_MP_THR_IDLE = "SPIN"

447.dealII (peak): "apache_stdccx4_2_1" src.alt was used.

447.dealII (base): "apache_stdccx4_2_1" src.alt was used.

Base Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 Server Module (Intel Xeon X5690 3.47 GHz)

SPECfp2006 = 64.0

SPECfp_base2006 = 58.6

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Jan-2011

Hardware Availability: Mar-2011

Software Availability: Nov-2010

Base Portability Flags (Continued)

465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_WORDS_LITTLEENDIAN
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast -xipo=2 -m64 -xautopar -xreduction

C++ benchmarks:

-fast -xipo=2 -m64 -xalias_level=compatible -library=no%Cstd
-I/data1/stdcxx-4.2.1/include -I/data1/stdcxx-4.2.1/build/include
-L/data1/stdcxx-4.2.1/build/lib -R/data1/stdcxx-4.2.1/build/lib -lstd8D

Fortran benchmarks:

-fast -xipo=2 -m64 -xautopar -xreduction

Benchmarks using both Fortran and C:

-fast(cc) -xipo=2 -m64 -xautopar -xreduction -fast(f90)

Base Other Flags

C benchmarks:

-V -# -xjobs=24

C++ benchmarks:

-verbose=diags,version -xjobs=24

Fortran benchmarks:

-V -v -xjobs=24

Benchmarks using both Fortran and C:

-V -# -xjobs=24 -v

Peak Compiler Invocation

C benchmarks:

cc

C++ benchmarks:

CC

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 Server Module (Intel Xeon X5690 3.47 GHz)

SPECfp2006 = 64.0

SPECfp_base2006 = 58.6

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Jan-2011

Hardware Availability: Mar-2011

Software Availability: Nov-2010

Peak Compiler Invocation (Continued)

Fortran benchmarks:
f90

Benchmarks using both Fortran and C:
cc f90

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_WORDS_LITTLEENDIAN
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -fast -xtarget=nehalem -xipo=2 -m64 -xalias_level=std
-xautopar -xreduction
```

```
470.lbm: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xautopar -xreduction
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap_mt64
```

```
482.sphinx3: -fast -xipo=2 -m64 -xpagesize=2M -xalias_level=std
-xrestrict -xprefetch=no%auto -xautopar -xreduction
```

C++ benchmarks:

```
444.namd: basepeak = yes
```

```
447.dealIII: -fast -xtarget=nehalem -xipo=2 -m64 -xpagesize=2M
-xalias_level=compatible -library=no%Cstd
-I/data1/stdcxx-4.2.1/include
-I/data1/stdcxx-4.2.1/build/include
-L/data1/stdcxx-4.2.1/build/lib
-R/data1/stdcxx-4.2.1/build/lib -lstd8D
```

```
450.soplex: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xpagesize=2M -xalias_level=compatible -library=stlport4
-m64
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 Server Module (Intel Xeon X5690 3.47 GHz)

SPECfp2006 = 64.0

SPECfp_base2006 = 58.6

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Jan-2011

Hardware Availability: Mar-2011

Software Availability: Nov-2010

Peak Optimization Flags (Continued)

453.povray: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xvector=no%simd -xalias_level=compatible
-library=stlport4 -qoption iropt -Atile:skewp
-qoption iropt -Ainline:cs=700

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -fast -xipo=2 -m64 -xpagesize=2M -xunroll=1
-xvector=no%simd

434.zeusmp: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=nehalem
-xipo=2 -m64 -xpagesize=2M -xautopar -xreduction

437.leslie3d: basepeak = yes

459.GemsFDTD: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xautopar -xreduction

465.tonto: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-stackvar -xprefetch=no%auto -xalias -xautopar -xreduction
-Qoption iropt -Aparallel:nthreads=6 -lumem

Benchmarks using both Fortran and C:

435.gromacs: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xvector=no%simd -xipo=2 -m64 -xpagesize=2M
-Qoption ube -fsimple=3 -xautopar -xreduction

436.cactusADM: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xtarget=nehalem -m64 -xautopar -xreduction -lmvec
-xpagesize=2M -W2,-Aparallel:nthreads=24
-Qoption iropt -Aparallel:nthreads=24 -lumem

454.calculix: -fast(cc) -fast(f90) -xipo=2 -m64 -xpagesize=2M
-xunroll=3 -xprefetch_level=2
-xprefetch_auto_type=indirect_array_access

481.wrf: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast(cc) -fast(f90)
-xipo=2 -m64 -xpagesize=4K -xprefetch=no%auto -xautopar
-xreduction -Qoption iropt -Aparallel:nthreads=6



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X6270 M2 Server Module (Intel Xeon X5690 3.47 GHz)

SPECfp2006 = 64.0

SPECfp_base2006 = 58.6

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: Jan-2011

Hardware Availability: Mar-2011

Software Availability: Nov-2010

Peak Other Flags

C benchmarks:

-V -# -xjobs=24

C++ benchmarks:

-verbose=diags,version -xjobs=24

Fortran benchmarks:

-V -v -xjobs=24

Benchmarks using both Fortran and C:

-V -# -xjobs=24 -v

The flags files that were used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.20110303.html

http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.20101027.html

You can also download the XML flags sources by saving the following links:

http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.20110303.xml

http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.20101027.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 16:17:18 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 3 March 2011.