



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu SPARC Enterprise M3000

SPECint®\_rate2006 = 37.2

SPECint\_rate\_base2006 = 33.7

CPU2006 license: 19


Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jan-2011

Hardware Availability: Apr-2011

Software Availability: Sep-2010



### Hardware

CPU Name: SPARC64 VII+  
 CPU Characteristics:  
 CPU MHz: 2860  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 5632 KB I+D on chip per chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 32 GB (8 x 4 GB, 2-way interleaved)  
 Disk Subsystem: 1 x 300 GB 10,000 RPM SAS  
 Other Hardware: None

### Software

Operating System: Oracle Solaris 10 9/10  
 Compiler: Oracle Solaris Studio 12.2  
 Auto Parallel: No  
 File System: ufs  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: None



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu  
SPARC Enterprise M3000

SPECint\_rate2006 = 37.2

SPECint\_rate\_base2006 = 33.7

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Jan-2011  
Hardware Availability: Apr-2011  
Software Availability: Sep-2010

## Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	1327	29.4	<b><u>1325</u></b>	<b><u>29.5</u></b>	1324	29.5	4	916	42.7	<b><u>918</u></b>	<b><u>42.6</u></b>	918	42.6
401.bzip2	4	<b><u>1513</u></b>	<b><u>25.5</u></b>	1518	25.4	1509	25.6	4	1389	27.8	1399	27.6	<b><u>1394</u></b>	<b><u>27.7</u></b>
403.gcc	4	1165	27.6	1159	27.8	<b><u>1160</u></b>	<b><u>27.7</u></b>	4	1058	30.4	1045	30.8	<b><u>1046</u></b>	<b><u>30.8</u></b>
429.mcf	4	789	46.2	789	46.2	<b><u>789</u></b>	<b><u>46.2</u></b>	4	732	49.8	<b><u>733</u></b>	<b><u>49.8</u></b>	735	49.6
445.gobmk	4	1187	35.4	1199	35.0	<b><u>1187</u></b>	<b><u>35.4</u></b>	4	<b><u>1075</u></b>	<b><u>39.0</u></b>	1066	39.4	1077	39.0
456.hammer	4	1620	23.0	<b><u>1619</u></b>	<b><u>23.0</u></b>	1619	23.1	4	1605	23.3	<b><u>1605</u></b>	<b><u>23.3</u></b>	1605	23.3
458.sjeng	4	1821	26.6	1822	26.6	<b><u>1822</u></b>	<b><u>26.6</u></b>	4	<b><u>1617</u></b>	<b><u>29.9</u></b>	1618	29.9	1616	30.0
462.libquantum	4	647	128	646	128	<b><u>647</u></b>	<b><u>128</u></b>	4	589	141	<b><u>588</u></b>	<b><u>141</u></b>	588	141
464.h264ref	4	1839	48.1	<b><u>1846</u></b>	<b><u>48.0</u></b>	1857	47.7	4	<b><u>1754</u></b>	<b><u>50.5</u></b>	1752	50.5	1757	50.4
471.omnetpp	4	<b><u>1390</u></b>	<b><u>18.0</u></b>	1385	18.1	1392	18.0	4	<b><u>1262</u></b>	<b><u>19.8</u></b>	1262	19.8	1263	19.8
473.astar	4	1203	23.3	<b><u>1203</u></b>	<b><u>23.3</u></b>	1205	23.3	4	1126	24.9	<b><u>1125</u></b>	<b><u>25.0</u></b>	1124	25.0
483.xalancbmk	4	<b><u>697</u></b>	<b><u>39.6</u></b>	699	39.5	697	39.6	4	<b><u>679</u></b>	<b><u>40.6</u></b>	680	40.6	677	40.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

Oracle Solaris Studio 12.2 is distributed with mandatory OS patches  
118683-05 119963-20 120753-08  
Oracle Solaris Studio 12.2 and patches are available at  
<http://oracle.com/goto/solarisstudio>

## Submit Notes

Processes were assigned to specific processors using 'pbind' commands. The config file option 'submit' was used, along with a list of processors in the 'BIND' variable, to generate the pbind commands. (For details, please see the config file.)

## Operating System Notes

ulimit -s 131072 was used to limit the space consumed by the stack (and therefore make more space available to the heap).

System Tunables:  
(/etc/system parameters)

tune\_t\_fsflushr=10  
Controls how many seconds elapse between runs of the page flush daemon, fsflush.

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**  
**SPARC Enterprise M3000**

**SPECint\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 33.7**

**CPU2006 license:** 19  
**Test sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test date:** Jan-2011  
**Hardware Availability:** Apr-2011  
**Software Availability:** Sep-2010

## Operating System Notes (Continued)

autoup=600  
Causes pages older than the listed number of seconds to be written by fsflush.  
bufhwm=3000  
Memory byte limit for caching I/O buffers.  
segmap\_percent=1  
Set maximum percent memory for file system cache.

### Other System Settings:

The "webconsole" service was turned off using  
svcadm disable webconsole

## Platform Notes

Memory is 2-way interleaved by filling all slots with the same capacity DIMMs.

This result is measured on a SPARC Enterprise M3000 server from Fujitsu. The SPARC Enterprise M3000 server from Oracle and from Fujitsu are electrically equivalent.

## Base Compiler Invocation

C benchmarks:  
cc

C++ benchmarks:  
CC

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_SOLARIS\_SPARC  
403.gcc: -DSPEC\_CPU\_SOLARIS  
462.libquantum: -DSPEC\_CPU\_SOLARIS  
483.xalancbmk: -DSPEC\_CPU\_SOLARIS

## Base Optimization Flags

C benchmarks:  
-fast -xO4 -fma=fused -xipo=2 -xpagesize=4M -xalias\_level=std  
-xunroll=12 -xprefetch=latx:0.5 -l12amm

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**  
**SPARC Enterprise M3000**

**SPECint\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 33.7**

**CPU2006 license:** 19  
**Test sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test date:** Jan-2011  
**Hardware Availability:** Apr-2011  
**Software Availability:** Sep-2010

## Base Optimization Flags (Continued)

C++ benchmarks:

```
-library=stlport4 -M /usr/lib/ld/map.bssalign -fast -xO4 -fma=fused  
-xipo=2 -xpagesize=4M -xdepend -xalias_level=compatible -xunroll=8  
-xprefetch=no%auto -lfast
```

## Base Other Flags

C benchmarks:

```
-xjobs=2 -V -#
```

C++ benchmarks:

```
-xjobs=2 -verbose=diags,version
```

## Peak Compiler Invocation

C benchmarks:

```
cc
```

C++ benchmarks:

```
CC
```

## Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_SOLARIS_SPARC  
403.gcc: -DSPEC_CPU_SOLARIS  
462.libquantum: -DSPEC_CPU_SOLARIS  
483.xalancbmk: -DSPEC_CPU_SOLARIS
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -M /usr/lib/ld/map.bssalign -xipo=2 -xO4  
-xalias_level=std -xrestrict -Xc -xprefetch=no%auto  
-lfast -ll2amm -lbsdmalloc
```

```
401.bzip2: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -xO4 -xchip=generic -xalias_level=strong
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**  
**SPARC Enterprise M3000**

**SPECint\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 33.7**

**CPU2006 license:** 19  
**Test sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test date:** Jan-2011  
**Hardware Availability:** Apr-2011  
**Software Availability:** Sep-2010

## Peak Optimization Flags (Continued)

403.gcc: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -xipo=2 -xO4 -xalias\_level=std  
-xprefetch=latx:0.5 -xunroll=2 -l12amm

429.mcf: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -M /usr/lib/ld/map.bssalign -xipo=2  
-xchip=generic -xprefetch\_auto\_type=indirect\_array\_access  
-xprefetch=latx:0.1 -W2,-Apf:l1list=3 -W2,-Apf:notinrl1list  
-Wc,-Qlp-prt=1 -Wc,-Qlp-prwt=3 -lfast -lbsdmalloc

445.gobmk: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -M /usr/lib/ld/map.bssalign -xalias\_level=std  
-xrestrict -xprefetch=latx:1 -xunroll=12 -lfast

456.hmmer: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -xipo=2 -xalias\_level=std -xprefetch\_level=2  
-xunroll=12

458.sjeng: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -xipo=2 -xO4 -xinline= -xprefetch=no%auto  
-xunroll=9 -l12amm

462.libquantum: -fast -fma=fused -xpagesize=4M -xalias\_level=std -xipo=2  
-xchip=generic -xprefetch=no%auto -xunroll=10 -lbsdmalloc

464.h264ref: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -xipo=2 -xvector -xalias\_level=std  
-xprefetch=latx:1.2 -l12amm

### C++ benchmarks:

471.omnetpp: -library=stlport4 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -xalias\_level=compatible  
-M /usr/lib/ld/map.bssalign -xipo=1 -xO4  
-Qoption cg -Qlp-av=0 -xprefetch=latx:1.2 -xunroll=5  
-lfast -lbsdmalloc

473.astar: -library=stlport4 -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -fma=fused  
-xpagesize=4M -xalias\_level=compatible  
-M /usr/lib/ld/map.bssalign -xlinkopt -xprefetch=latx:0.1  
-xunroll=10 -lfast

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**  
**SPARC Enterprise M3000**

**SPECint\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 33.7**

**CPU2006 license:** 19  
**Test sponsor:** Fujitsu  
**Tested by:** Fujitsu

**Test date:** Jan-2011  
**Hardware Availability:** Apr-2011  
**Software Availability:** Sep-2010

## Peak Optimization Flags (Continued)

```
483.xalanbmk: -library=stlport4 -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -fma=fused
-xpagesize=4M -xalias_level=compatible -xipo=2 -xO4
-xprefetch=no%auto -lfast
```

## Peak Other Flags

C benchmarks:  
-xjobs=2 -V -#

C++ benchmarks:  
-xjobs=2 -verbose=diags,version

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20110413.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.2-SPARC.20110413.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 19:17:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 12 April 2011.