



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R430 F2 (Intel Xeon X5675, 3.46 GHz)

SPECfp®2006 = 59.2

SPECfp_base2006 = 58.2

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date: Mar-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011



Hardware

CPU Name: Intel Xeon X5675
CPU Characteristics: Intel Turbo Boost Technology up to 3.46 GHz
CPU MHz: 3067
FPU: Integrated
CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: SUSE Linux Enterprise Server 11 SP1 (x86_64), Kernel 2.6.32.12-0.7-default
Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0 Update 3
Auto Parallel: Yes
File System: ext3
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 59.2

NovaScale R430 F2 (Intel Xeon X5675, 3.46 GHz)

SPECfp_base2006 = 58.2

CPU2006 license: 20

Test date: Mar-2011

Test sponsor: Bull SAS

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Apr-2011

L3 Cache: 12 MB I+D on chip per chip
 Other Cache: None
 Memory: 48 GB (6 x 8 GB 2Rx4 PC3-10600R-9, ECC)
 Disk Subsystem: 1 x 146 GB 15000 RPM SAS
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	77.5	175	78.3	174	<u>77.7</u>	<u>175</u>	76.1	179	73.3	185	<u>75.7</u>	<u>180</u>
416.gamess	767	25.5	<u>765</u>	<u>25.6</u>	762	25.7	<u>654</u>	<u>29.9</u>	654	30.0	654	29.9
433.milc	166	55.2	167	55.0	<u>167</u>	<u>55.1</u>	164	55.9	165	55.8	<u>165</u>	<u>55.8</u>
434.zeusmp	87.9	104	88.9	102	<u>88.1</u>	<u>103</u>	87.9	104	88.9	102	<u>88.1</u>	<u>103</u>
435.gromacs	304	23.5	<u>303</u>	<u>23.6</u>	302	23.6	282	25.3	<u>282</u>	<u>25.3</u>	282	25.3
436.cactusADM	52.5	228	<u>52.5</u>	<u>228</u>	52.7	227	52.5	228	<u>52.5</u>	<u>228</u>	52.7	227
437.leslie3d	81.2	116	80.4	117	<u>80.4</u>	<u>117</u>	81.2	116	80.4	117	<u>80.4</u>	<u>117</u>
444.namd	382	21.0	<u>382</u>	<u>21.0</u>	382	21.0	376	21.3	375	21.4	<u>375</u>	<u>21.4</u>
447.dealII	263	43.5	264	43.4	<u>263</u>	<u>43.4</u>	263	43.5	264	43.4	<u>263</u>	<u>43.4</u>
450.soplex	239	35.0	240	34.8	<u>239</u>	<u>34.8</u>	239	35.0	240	34.8	<u>239</u>	<u>34.8</u>
453.povray	160	33.2	160	33.3	<u>160</u>	<u>33.3</u>	127	41.8	<u>126</u>	<u>42.2</u>	126	42.2
454.calculix	<u>258</u>	<u>32.0</u>	257	32.1	260	31.8	229	36.1	<u>229</u>	<u>36.1</u>	229	36.1
459.GemsFDTD	137	77.2	142	74.7	<u>140</u>	<u>75.9</u>	<u>107</u>	<u>99.2</u>	106	100	112	94.9
465.tonto	318	31.0	<u>320</u>	<u>30.8</u>	366	26.9	273	36.0	<u>273</u>	<u>36.0</u>	273	36.0
470.lbm	50.2	274	<u>50.2</u>	<u>274</u>	58.4	235	122	113	82.2	167	<u>122</u>	<u>113</u>
481.wrf	<u>213</u>	<u>52.4</u>	210	53.1	216	51.8	<u>213</u>	<u>52.4</u>	210	53.1	216	51.8
482.sphinx3	346	56.3	348	56.0	<u>347</u>	<u>56.2</u>	<u>305</u>	<u>63.9</u>	<u>313</u>	<u>62.3</u>	314	62.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages
echo 900 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
```

Platform Notes

BIOS Settings:

Power Management = Maximum Performance (Default = Active Power Controller)

Data Reuse = Disabled (Default = Enabled)

Logical Processor = Disabled (Default = Enabled)



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R430 F2 (Intel Xeon X5675, 3.46 GHz)

SPECfp2006 =

59.2

SPECfp_base2006 =

58.2

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date:

Mar-2011

Hardware Availability:

Feb-2011

Software Availability:

Apr-2011

General Notes

OMP_NUM_THREADS set to number of cores

Binaries were compiled on RHEL5.5

The Dell PowerEdge R410 and

the Bull NovaScale R430 F2 models are electronically equivalent.

The results have been measured on a Dell PowerEdge R410 model.

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R430 F2 (Intel Xeon X5675, 3.46 GHz)

SPECfp2006 =

59.2

SPECfp_base2006 =

58.2

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date:

Mar-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011

Base Optimization Flags (Continued)

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32
-ansi-alias

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -parallel
-ansi-alias -static -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias
-parallel

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R430 F2 (Intel Xeon X5675, 3.46 GHz)

SPECfp2006 =

59.2

SPECfp_base2006 =

58.2

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Dell Inc.

Test date:

Mar-2011

Hardware Availability: Feb-2011

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias
-B /usr/share/libhugelbfs/ -Wl,-melf_x86_64 -Wl,-hugelbfs-link=BDT

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -parallel
-static

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -opt-prefetch -parallel
-B /usr/share/libhugelbfs/ -Wl,-melf_x86_64 -Wl,-hugelbfs-link=BDT

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
-opt-malloc-options=3 -auto -unroll4
-B /usr/share/libhugelbfs/ -Wl,-melf_x86_64 -Wl,-hugelbfs-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32
-ansi-alias

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp2006 = 59.2

NovaScale R430 F2 (Intel Xeon X5675, 3.46 GHz)

SPECfp_base2006 = 58.2

CPU2006 license: 20

Test date: Mar-2011

Test sponsor: Bull SAS

Hardware Availability: Feb-2011

Tested by: Dell Inc.

Software Availability: Apr-2011

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20110524.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 23:57:44 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 August 2011.