



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.
E-Rack 8248, AMD Opteron 6174

SPECint®2006 = 21.6
SPECint_base2006 = 17.8

CPU2006 license: 3106


Test sponsor: E4 Computer Engineering S.p.A.

Tested by: Francesca Tartaglione

Test date: Aug-2011

Hardware Availability: Jun-2010

Software Availability: Jul-2011



Hardware

CPU Name: AMD Opteron 6174
 CPU Characteristics: 2200
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 48 cores, 4 chips, 12 cores/chip
 CPU(s) orderable: 2,4 chip
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 12 MB I+D on chip per chip, 6 MB shared / 6 cores
 Other Cache: None
 Memory: 256 GB (32 x 8 GB 2Rx4 PC3-10600R-9, ECC)
 Disk Subsystem: 2 x 1 TB SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Scientific Linux release 6.1, Kernel 2.6.32-131.0.15.el6
 Compiler: x86 Open64 4.2.5.2 Compiler Suite (from AMD)
 Auto Parallel: Yes
 File System: ext4
 System State: Run level 3 (Full multiuser with network)
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap 8.1 32-bit Library for Linux



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.

SPECint2006 = 21.6

E-Rack 8248, AMD Opteron 6174

SPECint_base2006 = 17.8

CPU2006 license: 3106

Test date: Aug-2011

Test sponsor: E4 Computer Engineering S.p.A.

Hardware Availability: Jun-2010

Tested by: Francesca Tartaglione

Software Availability: Jul-2011

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	706	13.8	707	13.8	703	13.9	537	18.2	537	18.2	537	18.2
401.bzip2	896	10.8	899	10.7	899	10.7	821	11.8	816	11.8	816	11.8
403.gcc	634	12.7	633	12.7	632	12.7	534	15.1	536	15.0	536	15.0
429.mcf	554	16.5	561	16.3	557	16.4	337	27.1	338	27.0	337	27.0
445.gobmk	778	13.5	778	13.5	777	13.5	676	15.5	675	15.5	676	15.5
456.hammer	535	17.4	530	17.6	531	17.6	336	27.8	336	27.8	337	27.7
458.sjeng	931	13.0	932	13.0	932	13.0	885	13.7	887	13.6	885	13.7
462.libquantum	146	142	146	142	147	141	91.6	226	90.5	229	95.8	216
464.h264ref	1114	19.9	1122	19.7	1117	19.8	969	22.8	949	23.3	971	22.8
471.omnetpp	429	14.6	428	14.6	428	14.6	453	13.8	452	13.8	452	13.8
473.astar	571	12.3	573	12.3	573	12.3	560	12.5	560	12.5	558	12.6
483.xalancbmk	333	20.7	333	20.7	332	20.8	313	22.1	314	22.0	316	21.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.
See the configuration file for details.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size
cpuspeed stop was used to set the CPU frequency to its maximum.
Set vm/nr_hugepages=2000 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages

Platform Notes

Fan speed set to Full Speed in BIOS Setup.

General Notes

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/opt/amd/lib/gcc-lib/x86_64-open64-linux/4.2.5.2/64:/opt/amd/lib/gcc-lib/x86_64-open64-linux/4.2.5.2/32"
O64_OMP_AFFINITY_MAP = "0,1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,25,26,27,28,29,30,31,32,33,34,35,36,37,38,39,40,41,42,43,44,45,46,47"
O64_OMP_SPIN_USER_LOCK = "true"
The x86 Open64 Compiler Suite is only available from (and supported by) AMD at
<http://developer.amd.com/cpu/open64>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.

SPECint2006 =

21.6

E-Rack 8248, AMD Opteron 6174

SPECint_base2006 =

17.8

CPU2006 license: 3106

Test sponsor: E4 Computer Engineering S.p.A.

Tested by: Francesca Tartaglione

Test date: Aug-2011

Hardware Availability: Jun-2010

Software Availability: Jul-2011

Base Compiler Invocation

C benchmarks:
openc

C++ benchmarks:
openCC

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-march=barcelona -Ofast -apo -CG:local_sched_alg=1
-HP:bdt=2m:heap=2m,limit=450 -LNO:parallel_overhead=10000

C++ benchmarks:
-march=barcelona -Ofast -m32 -INLINE:aggressive=on -CG:cmp_peep=on
-L/opt/SmartHeap_8.1/lib -lsmarheap

Peak Compiler Invocation

C benchmarks:
openc

C++ benchmarks:
openCC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.	SPECint2006 =	21.6
E-Rack 8248, AMD Opteron 6174	SPECint_base2006 =	17.8

CPU2006 license: 3106	Test date:	Aug-2011
Test sponsor: E4 Computer Engineering S.p.A.	Hardware Availability:	Jun-2010
Tested by: Francesca Tartaglione	Software Availability:	Jul-2011

Peak Portability Flags (Continued)

445.gobmk: -DSPEC_CPU_LP64
 456.hmmer: -DSPEC_CPU_LP64
 458.sjeng: -DSPEC_CPU_LP64
 462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
 464.h264ref: -DSPEC_CPU_LP64
 483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -Ofast -IPA:plimit=20000 -LNO:opt=0
 -OPT:unroll_times_max=8 -OPT:unroll_size=256
 -OPT:unroll_level=2 -OPT:keep_ext=on -WOPT:if_conv=0
 -CG:local_sched_alg=1 -CG:unroll_fb_req=on
 -HP:bdtd=2m:heap=2m

401.bzip2: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -O3 -OPT:alias=disjoint
 -OPT:goto=off -CG:local_sched_alg=1 -HP:bdtd=2m:heap=2m

403.gcc: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -Ofast -LNO:trip_count=256
 -LNO:prefetch_ahead=10 -CG:cmp_peep=on -m32
 -HP:bdtd=2m:heap=2m -GRA:unspill=on -IPA:small_pu=200

429.mcf: -march=barcelona -O3 -ipa -INLINE:aggressive=on
 -CG:gcm=off -GRA:prioritize_by_density=on -m32
 -HP:bdtd=2m:heap=2m

445.gobmk: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -O3 -OPT:alias=restrict
 -OPT:unroll_times_max=8 -OPT:unroll_size=256
 -OPT:unroll_level=2 -OPT:keep_ext=on -ipa -IPA:plimit=750
 -IPA:min_hotness=300 -IPA:pu_reorder=1 -LNO:prefetch=1
 -LNO:ignore_feedback=off -CG:p2align=on
 -CG:unroll_fb_req=on -HP:bdtd=2m:heap=2m

456.hmmer: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -Ofast -LNO:prefetch=0
 -OPT:alias=disjoint -OPT:unroll_times_max=8
 -OPT:unroll_size=256 -OPT:unroll_level=2 -OPT:keep_ext=on
 -CG:local_sched_alg=1 -CG:cflow=0
 -CG:push_pop_int_saved_regs=off -CG:cmp_peep=on
 -HP:bdtd=2m:heap=2m

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.	SPECint2006 =	21.6
E-Rack 8248, AMD Opteron 6174	SPECint_base2006 =	17.8

CPU2006 license: 3106	Test date:	Aug-2011
Test sponsor: E4 Computer Engineering S.p.A.	Hardware Availability:	Jun-2010
Tested by: Francesca Tartaglione	Software Availability:	Jul-2011

Peak Optimization Flags (Continued)

458.sjeng: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -O3 -ipa -LNO:ignore_feedback=off
 -LNO:full_unroll=10 -LNO:fusion=0 -LNO:fission=2
 -IPA:pu_reorder=2 -IPA:min_hotness=32 -CG:ptr_load_use=0
 -OPT:unroll_times_max=8 -INLINE:aggressive=on
 -HP:bdt=2m:heap=2m

462.libquantum: -march=barcelona -Ofast -apo -LNO:pf2=0 -CG:gcm=off
 -CG:use_prefetchnta=on -CG:cmp_peep=on -WOPT:aggstr=0
 -OPT:alias=disjoint -INLINE:aggressive=on -IPA:space=1000
 -IPA:plimit=20000 -mso

464.h264ref: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -O3 -IPA:plimit=20000
 -OPT:alias=disjoint -LNO:prefetch=0 -CG:ptr_load_use=0
 -CG:push_pop_int_saved_regs=off -HP:bdt=2m:heap=2m

C++ benchmarks:

471.omnetpp: -march=barcelona -Ofast -CG:gcm=off -INLINE:aggressive=on
 -WOPT:if_conv=0 -m32 -HP:bdt=2m:heap=2m

473.astar: -march=barcelona -fb_create fbdata(pass 1)
 -fb_opt fbdata(pass 2) -Ofast -TENV:frame_pointer=off
 -WOPT:if_conv=0 -GRA:optimize_boundary=on
 -OPT:alias=disjoint -INLINE:aggressive=on
 -IPA:small_pu=3000 -IPA:plimit=3000 -m32
 -HP:bdt=2m:heap=2m

483.xalancbmk: -march=barcelona -Ofast -INLINE:aggressive=on -m32
 -CG:cmp_peep=on -GRA:unspill=on -TENV:frame_pointer=off
 -fno-emit-exceptions -L/opt/SmartHeap_8.1/lib -lsmarheap

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/x86-open64-423-flags-speed-revA.20101207.html>
<http://www.spec.org/cpu2006/flags/E4ComputerEngineering-amd-platform.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/x86-open64-423-flags-speed-revA.20101207.xml>
<http://www.spec.org/cpu2006/flags/E4ComputerEngineering-amd-platform.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

E4 Computer Engineering S.p.A.	SPECint2006 =	21.6
E-Rack 8248, AMD Opteron 6174	SPECint_base2006 =	17.8

CPU2006 license: 3106

Test sponsor: E4 Computer Engineering S.p.A.

Tested by: Francesca Tartaglione

Test date: Aug-2011

Hardware Availability: Jun-2010

Software Availability: Jul-2011

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 21:37:33 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 27 September 2011.