



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/A1080a-D (Intel Xeon E7-8870)

**SPECfp®\_rate2006 = 339**

**SPECfp\_rate\_base2006 = 328**

**CPU2006 license:** 9006


**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Nov-2011

**Hardware Availability:** Nov-2011

**Software Availability:** May-2011



## Hardware

CPU Name: Intel Xeon E7-8870  
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
CPU MHz: 2400  
FPU: Integrated  
CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2,3,4 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

## Software

Operating System: Red Hat Enterprise Linux Server release 6.1, Kernel 2.6.32-131.0.15.el6.x86\_64 on an x86\_64  
Compiler: C/C++/Fortran: Version 12.0.4.191 of Intel Compiler XE Build 20110427  
Auto Parallel: No  
File System: ext4  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/A1080a-D (Intel Xeon E7-8870)

**SPECfp\_rate2006 = 339**

**CPU2006 license:** 9006

**Test date:** Nov-2011

**Test sponsor:** NEC Corporation

**Hardware Availability:** Nov-2011

**Tested by:** NEC Corporation

**Software Availability:** May-2011

L3 Cache: 30 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 128 GB (32 x 4 GB 2Rx4 PC3-8500R-7, ECC)  
 Disk Subsystem: 2x300 GB SAS, 10000 RPM, RAID 0  
 Other Hardware: None

Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	40	2177	250	2507	217	<b>2444</b>	<b>222</b>	40	1942	280	<b>2067</b>	<b>263</b>	2419	225
416.gamess	40	1918	408	1865	420	<b>1912</b>	<b>410</b>	40	1818	431	<b>1820</b>	<b>430</b>	1855	422
433.milc	40	<b>1303</b>	<b>282</b>	1334	275	1301	282	40	1308	281	1307	281	<b>1308</b>	<b>281</b>
434.zeusmp	40	896	406	<b>895</b>	<b>407</b>	895	407	40	896	406	<b>895</b>	<b>407</b>	895	407
435.gromacs	40	764	374	762	375	<b>763</b>	<b>374</b>	40	746	383	<b>746</b>	<b>383</b>	746	383
436.cactusADM	40	1162	411	1195	400	<b>1185</b>	<b>403</b>	40	1162	411	1195	400	<b>1185</b>	<b>403</b>
437.leslie3d	40	1849	203	<b>1850</b>	<b>203</b>	1850	203	40	1860	202	<b>1851</b>	<b>203</b>	1848	203
444.namd	40	911	352	921	348	<b>919</b>	<b>349</b>	40	902	356	<b>901</b>	<b>356</b>	895	358
447.dealII	40	700	654	705	649	<b>702</b>	<b>652</b>	40	761	601	762	601	<b>762</b>	<b>601</b>
450.soplex	40	<b>1559</b>	<b>214</b>	1608	207	1538	217	40	<b>1381</b>	<b>242</b>	1396	239	1380	242
453.povray	40	<b>399</b>	<b>534</b>	399	533	397	536	40	<b>327</b>	<b>651</b>	326	654	327	650
454.calculix	40	720	458	<b>721</b>	<b>458</b>	722	457	40	720	458	<b>721</b>	<b>458</b>	722	457
459.GemsFDTD	40	3442	123	2460	173	<b>2927</b>	<b>145</b>	40	3442	123	2460	173	<b>2927</b>	<b>145</b>
465.tonto	40	<b>852</b>	<b>462</b>	852	462	852	462	40	<b>841</b>	<b>468</b>	840	469	843	467
470.lbm	40	2961	186	2952	186	<b>2956</b>	<b>186</b>	40	2937	187	<b>2937</b>	<b>187</b>	2936	187
481.wrf	40	1258	355	<b>1253</b>	<b>356</b>	1252	357	40	1258	355	<b>1253</b>	<b>356</b>	1252	357
482.sphinx3	40	<b>2245</b>	<b>347</b>	2247	347	2245	347	40	<b>2093</b>	<b>373</b>	<b>2092</b>	<b>373</b>	2090	373

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
 numactl was used to bind copies to the cores

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stack size to unlimited prior to run
echo 1 > /proc/sys/vm/zone_reclaim_mode
'mount -t hugetlbfs nodev /mnt/hugepages' was used to enable large pages
echo 18000 > /proc/sys/vm/nr_hugepages
export HUGETLB_MORECORE=yes
export LD_PRELOAD=/usr/lib64/libhugetlbfs.so
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/A1080a-D (Intel Xeon E7-8870)

**SPECfp\_rate2006 = 339**

**SPECfp\_rate\_base2006 = 328**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Nov-2011

**Hardware Availability:** Nov-2011

**Software Availability:** May-2011

## Platform Notes

Patrol Scrubbing set to disabled in Maintenance Console

## General Notes

The Express5800/A1080a-S and the Express5800/A1080a-D models are electronically equivalent.  
The results have been measured on the Express5800/A1080a-S model.  
Binaries were compiled on RHEL 5.6

## Base Compiler Invocation

C benchmarks:

    icc -m64

C++ benchmarks:

    icpc -m64

Fortran benchmarks:

    ifort -m64

Benchmarks using both Fortran and C:

    icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
    433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
    444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
    465.tonto: -DSPEC\_CPU\_LP64  
    470.lbm: -DSPEC\_CPU\_LP64  
    481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/A1080a-D (Intel Xeon E7-8870)

**SPECfp\_rate2006 = 339**

CPU2006 license: 9006

Test date: Nov-2011

Test sponsor: NEC Corporation

Hardware Availability: Nov-2011

Tested by: NEC Corporation

Software Availability: May-2011

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/A1080a-D (Intel Xeon E7-8870)

**SPECfp\_rate2006 = 339**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Nov-2011

**Hardware Availability:** Nov-2011

**Software Availability:** May-2011

## Peak Portability Flags (Continued)

470.lbm: -DSPEC\_CPU\_LP64

481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
-ansi-alias -opt-prefetch -static -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
-B /usr/share/libhugetlbfss/ -Wl,-hugetlbfss-link=BDT

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias  
-B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

Fortran benchmarks:

410.bwaves: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div  
-B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/A1080a-D (Intel Xeon E7-8870)

**SPECfp\_rate2006 = 339**

**CPU2006 license:** 9006

**Test date:** Nov-2011

**Test sponsor:** NEC Corporation

**Hardware Availability:** Nov-2011

**Tested by:** NEC Corporation

**Software Availability:** May-2011

## Peak Optimization Flags (Continued)

459.GemsFDTD: basepeak = yes

```
465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -auto
            -inline-alloc -opt-malloc-options=3
            -B /usr/share/libhugetlbfs/ -Wl,-melf_x86_64 -Wl,-hugetlbfs-link=BDT
```

Benchmarks using both Fortran and C:

```
435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
              -no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch
              -static -auto-ilp32
```

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110705.html>  
<http://www.spec.org/cpu2006/flags/NEC-platform-linux64-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20110705.xml>  
<http://www.spec.org/cpu2006/flags/NEC-platform-linux64-revC.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Thu Jul 24 01:18:44 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 December 2011.