



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp®2006 =

SPECfp\_base2006 =

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the or can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

- 410.bwaves |
- 416.gamess |
- 433.milc |
- 434.zeusmp |
- 435.gromacs |
- 436.cactusADM |
- 437.leslie3d |
- 444.namd |
- 447.dealII |
- 450.soplex |
- 453.povray |
- 454.calculix |
- 459.gcc |
- 465.totso |
- 470.lbm |
- 481.wrf |
- 482.sphinx3 |



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 = **NC**

SPECfp\_base2006 = **NC**

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

### Hardware

CPU Name: Intel Xeon E7-8870  
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
CPU MHz: 2400  
FPU: Integrated  
CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core  
L3 Cache: 30 MB I+D on chip per chip  
Other Cache: None  
Memory: 256 GB (32 x 8 GB 4Rx PC3-8500R-7, ECC)  
Disk Subsystem: 1 x 300 GB SAS, 10000 RPM  
Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
2.6.32-220.el6.x86\_64  
Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux;  
Fortran: Version 12.1.0.225 of Intel Fortran Studio XE for Linux  
Auto Parallel: Yes  
File System: ext4  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

**Non-Compliant**



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 = **NC**

SPECfp\_base2006 = **NC**

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Feb-2012

Hardware Availability: May-2011

Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

### Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
416.gamess	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
433.milc	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
434.zeusmp	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
435.gromacs	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
436.cactusADM	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
437.leslie3d	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
444.namd	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
447.dealII	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
450.soplex	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
453.povray	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
454.calculix	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
459.GemsFDTD	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
465.tonto	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
470.lbm	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
481.wrf	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
482.sphinx3	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC

Results are listed in the order in which they were run. Bold underlined text indicates a median measurement.

### Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

### Platform Notes

Turbo Boost Power Optimization set to Traditional in BIOS  
Sysinfo program /cpu2006.1.2/config/sysinfo.rev6800  
\$Rev: 6800 \$ \$Date:: 2011-10-11 #\$ 6f2ebdff5032aaa42e583f96b07f99d3  
running on megallon-pete Fri Feb 17 18:44:09 2012

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 =

SPECfp\_base2006 =

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

## Platform Notes (Continued)

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name      : Intel(R) Xeon(R) CPU E7- 8800 @ 2.40GHz
 2 "physical id"s (chips)
 40 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores      : 10
  siblings       : 20
  physical 0:    cores 0 1 2 3 4 5 6 7 8 9 16 17 18 24 25
  physical 1:    cores 0 1 2 3 4 5 6 7 8 9 16 17 18 24 25
cache size      : 30720 KB
```

```
From /proc/meminfo
MemTotal:        2645000 kB
HugePages_Total: 0
Hugepagesize:    2048 kB
```

```
/usr/bin/lsh_release -a
Red Hat Enterprise Linux Server release 6.2 (Santiago)
```

```
From /etc/*release /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
Linux megallon-pete 2.6.32-220.el6.x86_64 #1 SMP Wed Nov 9 08:03:13 EST 2011
x86_64 x86_64 x86_64 GNU/Linux
```

run-level 3 Feb 15 17:35

```
SPEC is set to: /cpu2006.1.2
Filesystem      Type      Size  Used Avail Use% Mounted on
/dev/mapper/vg_megallonpete-lv_root
                ext4      264G  83G 169G  33% /
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 =

SPECfp\_base2006 =

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

## Platform Notes (Continued)

Additional information from dmidecode:

Memory:

32x Hynix HMT31GR7BFR8A-G7 8 GB 10657 4 1 1 K

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=line,scatter"  
LD\_LIBRARY\_PATH = "/cpu2006.1.2/libs/22:/cpu2006.1.2/libs/64"  
OMP\_NUM\_THREADS = "20"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RHEL5.5

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 =

SPECfp\_base2006 =

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

```
C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 =

SPECfp\_base2006 =

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

## Peak Compiler Invocation

C benchmarks:  
icc -m64  
C++ benchmarks:  
icpc -m64  
Fortran benchmarks:  
ifort -m64  
Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:  
453.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32 -ansi-alias  
470.lbm: basepeak = yes  
483.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias -parallel  
C++ benchmarks:  
444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

Continued on next page





# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 =

SPECfp\_base2006 =

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

## Peak Optimization Flags (Continued)

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll14

with Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes





# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3690 X5 (Intel Xeon E7-2870, 2.40 GHz)

SPECfp2006 =

SPECfp\_base2006 =

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2012  
Hardware Availability: May-2011  
Software Availability: Feb-2012

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the submitter reported that the result does not meet the 3 month availability requirement in the SPEC CPU2006 run rules, because the tested processor was not supported on this platform within three months of publication. Results using the processor can be found at <http://www.spec.org/cpu2006/results/res2012q3/cpu2006-2012>**

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>  
<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-WSM-A.20120328.html>

You can also download the XML flags sources using the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>  
<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-WSM-A.20120328.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 02:55:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 27 March 2012.