



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Itautec**

**SPECint®\_rate2006 = 89.6**

Servidor Itautec MX225 (Intel Xeon E5-2603)

**SPECint\_rate\_base2006 = 85.9**

CPU2006 license: 9001


Test date: Feb-2013

Test sponsor: Itautec

Hardware Availability: Jun-2012

Tested by: Itautec

Software Availability: Jun-2012



<b>Hardware</b>		<b>Software</b>	
CPU Name:	Intel Xeon E5-2603	Operating System:	Red Hat Enterprise Linux Server Release 6.3, 2.6.32-279.el6.x86_64
CPU Characteristics:		Compiler:	C/C++: Version 12.1.0 of Intel Compiler XE Build 20111011
CPU MHz:	1800	Auto Parallel:	No
FPU:	Integrated	File System:	ext4
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip	System State:	Run level 3 (multi-user)
CPU(s) orderable:	1,2 chips	Base Pointers:	32-bit
Primary Cache:	32 KB I + 32 KB D on chip per core	Peak Pointers:	32/64-bit
Secondary Cache:	256 KB I+D on chip per core	Other Software:	Microquill SmartHeap V8.1
L3 Cache:	10 MB I+D on chip per chip		
Other Cache:	None		
Memory:	32 GB (8 x 4 GB 2Rx4 PC3-10600R-9, ECC, running at 1066 MHz and CL7)		
Disk Subsystem:	1000 GB, SATA-3, 7200 RPM		
Other Hardware:	None		



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautech

**SPECint\_rate2006 = 89.6**

Servidor Itautech MX225 (Intel Xeon E5-2603)

**SPECint\_rate\_base2006 = 85.9**

CPU2006 license: 9001

Test date: Feb-2013

Test sponsor: Itautech

Hardware Availability: Jun-2012

Tested by: Itautech

Software Availability: Jun-2012

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	656	59.6	<b>656</b>	<b>59.5</b>	658	59.4	4	530	73.8	<b>529</b>	<b>73.9</b>	529	73.9
401.bzip2	4	<b>860</b>	<b>44.9</b>	859	44.9	861	44.9	4	<b>828</b>	<b>46.6</b>	826	46.7	828	46.6
403.gcc	4	449	71.8	450	71.5	<b>450</b>	<b>71.5</b>	4	452	71.2	453	71.1	<b>452</b>	<b>71.2</b>
429.mcf	4	248	147	<b>248</b>	<b>147</b>	247	147	4	248	147	<b>248</b>	<b>147</b>	247	147
445.gobmk	4	787	53.3	<b>787</b>	<b>53.3</b>	788	53.3	4	<b>774</b>	<b>54.2</b>	774	54.2	774	54.2
456.hmmer	4	357	104	<b>359</b>	<b>104</b>	362	103	4	332	113	332	112	<b>332</b>	<b>112</b>
458.sjeng	4	834	58.1	835	58.0	<b>834</b>	<b>58.1</b>	4	803	60.3	<b>804</b>	<b>60.2</b>	804	60.2
462.libquantum	4	<b>158</b>	<b>524</b>	158	525	158	523	4	<b>158</b>	<b>524</b>	158	525	158	523
464.h264ref	4	807	110	<b>817</b>	<b>108</b>	817	108	4	792	112	<b>792</b>	<b>112</b>	781	113
471.omnetpp	4	419	59.6	419	59.7	<b>419</b>	<b>59.7</b>	4	382	65.4	<b>381</b>	<b>65.6</b>	378	66.1
473.astar	4	<b>565</b>	<b>49.7</b>	567	49.5	562	49.9	4	<b>565</b>	<b>49.7</b>	567	49.5	562	49.9
483.xalancbmk	4	<b>262</b>	<b>106</b>	262	105	261	106	4	<b>262</b>	<b>106</b>	262	105	261	106

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.  
Large pages were not enabled for this run

## Platform Notes

```
Sysinfo program /home/rcaaneca/cpu2006/Docs/sysinfo
$Rev: 6775 $ $Date::: 2011-08-16 #$
running on mx225 Mon Feb 25 15:59:46 2013
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E5-2603 0 @ 1.80GHz
        1 "physical id"s (chips)
        4 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
        cpu cores : 4
        siblings  : 4
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

SPECint\_rate2006 = 89.6

Servidor Itaute MX225 (Intel Xeon E5-2603)

SPECint\_rate\_base2006 = 85.9

CPU2006 license: 9001

Test date: Feb-2013

Test sponsor: Itaute

Hardware Availability: Jun-2012

Tested by: Itaute

Software Availability: Jun-2012

## Platform Notes (Continued)

```
physical 0: cores 0 1 2 3
cache size : 10240 KB

From /proc/meminfo
MemTotal:      32824280 kB
HugePages_Total:      0
Hugepagesize:     2048 kB

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.3 (Santiago)

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.3 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.3 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
Linux mx225 2.6.32-279.el6.x86_64 #1 SMP Wed Jun 13 18:24:36 EDT 2012 x86_64
x86_64 x86_64 GNU/Linux

run-level 3 Feb 25 15:56

SPEC is set to: /home/rcaaneca/cpu2006
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/mapper/vg_mx225-lv_home
                  ext4   836G  2.2G  791G   1%  /home

(End of data from sysinfo program)
```

## General Notes

This result was measured on the Servidor Itaute MX225.  
The Servidor Itaute MX215 and the Servidor Itaute MX225  
are electronically equivalent.

## Base Compiler Invocation

C benchmarks:  
icc -m32

C++ benchmarks:  
icpc -m32

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

SPECint\_rate2006 = 89.6

Servidor Itaute MX225 (Intel Xeon E5-2603)

SPECint\_rate\_base2006 = 85.9

CPU2006 license: 9001

Test date: Feb-2013

Test sponsor: Itaute

Hardware Availability: Jun-2012

Tested by: Itaute

Software Availability: Jun-2012

## Base Portability Flags (Continued)

462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
-Wl,-z,muldefs -L/home/rcaenca/sh/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

SPECint\_rate2006 = 89.6

Servidor Itaute MX225 (Intel Xeon E5-2603)

SPECint\_rate\_base2006 = 85.9

CPU2006 license: 9001

Test date: Feb-2013

Test sponsor: Itaute

Hardware Availability: Jun-2012

Tested by: Itaute

Software Availability: Jun-2012

## Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -opt-mem-layout-trans=3

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/home/rcaenca/sh/SmartHeap\_8.1/lib -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

SPECint\_rate2006 = 89.6

Servidor Itaute MX225 (Intel Xeon E5-2603)

SPECint\_rate\_base2006 = 85.9

CPU2006 license: 9001

Test date: Feb-2013

Test sponsor: Itaute

Hardware Availability: Jun-2012

Tested by: Itaute

Software Availability: Jun-2012

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/Itaute-Servidor\\_Itaute-Intel-Linux-Platform.html](http://www.spec.org/cpu2006/flags/Itaute-Servidor_Itaute-Intel-Linux-Platform.html)  
<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags sources by saving the following links:

[http://www.spec.org/cpu2006/flags/Itaute-Servidor\\_Itaute-Intel-Linux-Platform.xml](http://www.spec.org/cpu2006/flags/Itaute-Servidor_Itaute-Intel-Linux-Platform.xml)  
<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 14:14:06 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 26 March 2013.