



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp[®]2006 = **99.1**

PRIMERGY BX924 S4, Intel Xeon E5-2670 v2, 2.50 GHz

SPECfp_base2006 = **94.8**

CPU2006 license: 19


Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Oct-2013

Hardware Availability: Oct-2013

Software Availability: Sep-2013



Hardware

CPU Name: Intel Xeon E5-2670 v2
 CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz
 CPU MHz: 2500
 FPU: Integrated
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)
 2.6.32-358.11.1.el6.x86_64
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = **99.1**

PRIMERGY BX924 S4, Intel Xeon E5-2670 v2, 2.50 GHz

SPECfp_base2006 = **94.8**

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Oct-2013

Hardware Availability: Oct-2013

Software Availability: Sep-2013

L3 Cache: 25 MB I+D on chip per chip
 Other Cache: None
 Memory: 128 GB (16 x 8 GB 2Rx4 PC3-14900R-13, ECC)
 Disk Subsystem: 1 x SATA, 500 GB, 7200 RPM
 Other Hardware: None

System State: Run level 3 (multi-user)
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---------------|------------|-------------|-------------|-------------|-------------|-------------|------------|-------------|-------------|-------------|-------------|-------------|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 29.2 | 465 | 30.2 | 450 | <u>29.2</u> | <u>465</u> | 29.2 | 465 | 30.2 | 450 | <u>29.2</u> | <u>465</u> |
| 416.gamess | 642 | 30.5 | <u>643</u> | <u>30.5</u> | 643 | 30.5 | <u>550</u> | <u>35.6</u> | 547 | 35.8 | 550 | 35.6 |
| 433.milc | 137 | 66.9 | <u>137</u> | <u>67.0</u> | 137 | 67.1 | 136 | 67.6 | <u>136</u> | <u>67.7</u> | 135 | 68.2 |
| 434.zeusmp | 54.8 | 166 | 54.6 | 167 | <u>54.6</u> | <u>167</u> | 54.8 | 166 | 54.6 | 167 | <u>54.6</u> | <u>167</u> |
| 435.gromacs | 176 | 40.5 | <u>177</u> | <u>40.4</u> | 177 | 40.4 | 176 | 40.5 | <u>177</u> | <u>40.4</u> | 177 | 40.4 |
| 436.cactusADM | 18.5 | 647 | <u>18.7</u> | <u>640</u> | 18.9 | 634 | 18.5 | 647 | <u>18.7</u> | <u>640</u> | 18.9 | 634 |
| 437.leslie3d | 32.2 | 292 | <u>31.6</u> | <u>297</u> | 30.6 | 307 | 32.2 | 292 | <u>31.6</u> | <u>297</u> | 30.6 | 307 |
| 444.namd | 353 | 22.7 | <u>353</u> | <u>22.7</u> | 352 | 22.8 | 345 | 23.3 | <u>345</u> | <u>23.3</u> | 345 | 23.3 |
| 447.dealII | 216 | 53.0 | 216 | 52.9 | <u>216</u> | <u>53.0</u> | 216 | 53.0 | 216 | 52.9 | <u>216</u> | <u>53.0</u> |
| 450.soplex | 183 | 45.7 | 181 | 46.2 | <u>181</u> | <u>46.2</u> | 183 | 45.7 | 181 | 46.2 | <u>181</u> | <u>46.2</u> |
| 453.povray | 121 | 44.1 | 122 | 43.7 | <u>121</u> | <u>43.9</u> | <u>102</u> | <u>52.2</u> | 102 | 52.0 | 101 | 52.9 |
| 454.calculix | <u>189</u> | <u>43.7</u> | 189 | 43.7 | 188 | 43.9 | 175 | 47.2 | <u>175</u> | <u>47.2</u> | 175 | 47.1 |
| 459.GemsFDTD | 52.8 | 201 | 53.4 | 199 | <u>53.2</u> | <u>199</u> | 48.1 | 220 | 48.3 | 220 | <u>48.1</u> | <u>220</u> |
| 465.tonto | 273 | 36.0 | <u>274</u> | <u>36.0</u> | 274 | 35.9 | 223 | 44.1 | 220 | 44.8 | <u>220</u> | <u>44.6</u> |
| 470.lbm | 22.8 | 602 | <u>23.0</u> | <u>596</u> | 23.6 | 582 | 22.8 | 602 | <u>23.0</u> | <u>596</u> | 23.6 | 582 |
| 481.wrf | <u>109</u> | <u>102</u> | 110 | 102 | 109 | 103 | <u>109</u> | <u>102</u> | 110 | 102 | 109 | 103 |
| 482.sphinx3 | 273 | 71.3 | 275 | 70.8 | <u>275</u> | <u>71.0</u> | <u>275</u> | <u>71.0</u> | 273 | 71.3 | 277 | 70.4 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS configuration:
 Energy Performance = Performance
 Utilization Profile = Unbalanced

General Notes

Environment variables set by runspec before the start of the run:
 KMP_AFFINITY = "granularity=fine,compact,1,0"
 LD_LIBRARY_PATH = "/SPECcpu2006/libs/32:/SPECcpu2006/libs/64:/SPECcpu2006/sh"

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 99.1

PRIMERGY BX924 S4, Intel Xeon E5-2670 v2, 2.50 GHz

SPECfp_base2006 = 94.8

CPU2006 license: 19

Test date: Oct-2013

Test sponsor: Fujitsu

Hardware Availability: Oct-2013

Tested by: Fujitsu

Software Availability: Sep-2013

General Notes (Continued)

OMP_NUM_THREADS = "20"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

For information about Fujitsu please visit: <http://www.fujitsu.com>

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 99.1

PRIMERGY BX924 S4, Intel Xeon E5-2670 v2, 2.50 GHz

SPECfp_base2006 = 94.8

CPU2006 license: 19

Test date: Oct-2013

Test sponsor: Fujitsu

Hardware Availability: Oct-2013

Tested by: Fujitsu

Software Availability: Sep-2013

Base Optimization Flags

C benchmarks:

`-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias`

C++ benchmarks:

`-xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias`

Fortran benchmarks:

`-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch`

Benchmarks using both Fortran and C:

`-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias`

Peak Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: `-xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32
-ansi-alias`

470.lbm: `basepeak = yes`

482.sphinx3: `-xAVX -ipo -O3 -no-prec-div -unroll2 -ansi-alias
-parallel`

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 99.1

PRIMERGY BX924 S4, Intel Xeon E5-2670 v2, 2.50 GHz

SPECfp_base2006 = 94.8

CPU2006 license: 19

Test date: Oct-2013

Test sponsor: Fujitsu

Hardware Availability: Oct-2013

Tested by: Fujitsu

Software Availability: Sep-2013

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20131009.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20131009.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 99.1

PRIMERGY BX924 S4, Intel Xeon E5-2670 v2, 2.50 GHz

SPECfp_base2006 = 94.8

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Oct-2013

Hardware Availability: Oct-2013

Software Availability: Sep-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 17:53:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 November 2013.