



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei
Huawei Tecal RH2285H V2

SPECfp[®]2006 = 72.5
SPECfp_base2006 = 67.9

CPU2006 license: 3175


Test sponsor: Huawei

Tested by: Huawei

Test date: Mar-2014

Hardware Availability: Jan-2014

Software Availability: Nov-2013



Hardware

CPU Name: Intel Xeon E5-2450 v2
 CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz
 CPU MHz: 2500
 FPU: Integrated
 CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip
 CPU(s) orderable: 1,2 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)
 2.6.32-431.el6.x86_64
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei
Huawei Tecal RH2285H V2

SPECfp2006 = 72.5
SPECfp_base2006 = 67.9

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2014
Hardware Availability: Jan-2014
Software Availability: Nov-2013

L3 Cache: 20 MB I+D on chip per chip
Other Cache: None
Memory: 96 GB (12 x 8 GB 2Rx4 PC3-12800R-11, ECC)
Disk Subsystem: 1 x 500 GB SATA, 7200RPM
Other Hardware: None

System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>62.0</u>	<u>219</u>	48.8	278	63.8	213	<u>62.0</u>	<u>219</u>	48.8	278	63.8	213
416.gamess	<u>636</u>	<u>30.8</u>	643	30.5	635	30.9	537	36.5	<u>538</u>	<u>36.4</u>	538	36.4
433.milc	135	68.0	<u>135</u>	<u>68.0</u>	135	68.0	<u>134</u>	<u>68.4</u>	134	68.3	134	68.5
434.zeusmp	82.8	110	<u>82.8</u>	<u>110</u>	63.8	143	82.8	110	<u>82.8</u>	<u>110</u>	63.8	143
435.gromacs	<u>181</u>	<u>39.4</u>	181	39.5	198	36.1	<u>181</u>	<u>39.4</u>	181	39.5	198	36.1
436.cactusADM	50.9	235	55.1	217	<u>52.3</u>	<u>229</u>	50.9	235	55.1	217	<u>52.3</u>	<u>229</u>
437.leslie3d	104	90.5	<u>101</u>	<u>92.7</u>	72.2	130	104	90.5	<u>101</u>	<u>92.7</u>	72.2	130
444.namd	349	23.0	349	23.0	<u>349</u>	<u>23.0</u>	342	23.4	<u>342</u>	<u>23.4</u>	342	23.5
447.dealII	217	52.7	217	52.8	<u>217</u>	<u>52.7</u>	217	52.7	217	52.8	<u>217</u>	<u>52.7</u>
450.soplex	<u>190</u>	<u>43.9</u>	190	43.9	189	44.2	<u>190</u>	<u>43.9</u>	190	43.9	189	44.2
453.povray	<u>121</u>	<u>44.1</u>	121	43.9	120	44.5	<u>102</u>	<u>52.2</u>	102	52.0	99.6	53.4
454.calculix	245	33.6	<u>222</u>	<u>37.2</u>	220	37.4	167	49.4	<u>167</u>	<u>49.4</u>	167	49.4
459.GemsFDTD	75.2	141	<u>92.8</u>	<u>114</u>	114	93.4	75.2	141	<u>92.8</u>	<u>114</u>	114	93.4
465.tonto	359	27.4	277	35.6	<u>341</u>	<u>28.8</u>	217	45.4	<u>217</u>	<u>45.3</u>	218	45.0
470.lbm	<u>53.6</u>	<u>256</u>	48.8	281	58.0	237	<u>53.6</u>	<u>256</u>	48.8	281	58.0	237
481.wrf	<u>174</u>	<u>64.3</u>	171	65.3	181	61.8	<u>174</u>	<u>64.3</u>	171	65.3	181	61.8
482.sphinx3	338	57.7	<u>278</u>	<u>70.0</u>	277	70.3	<u>277</u>	<u>70.2</u>	382	51.1	<u>278</u>	<u>70.0</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS configuration:
Set Power Efficiency Mode to Performance
Sysinfo program /spec/config/sysinfo.rev6818
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191
running on localhost.localdomain Mon Mar 31 07:24:34 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei
Huawei Tecal RH2285H V2

SPECfp2006 = 72.5
SPECfp_base2006 = 67.9

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2014
Hardware Availability: Jan-2014
Software Availability: Nov-2013

Platform Notes (Continued)

```

From /proc/cpuinfo
  model name : Intel(R) Xeon(R) CPU E5-2450 v2 @ 2.50GHz
    2 "physical id"s (chips)
    16 "processors"
  cores, siblings (Caution: counting these is hw and system dependent. The
  following excerpts from /proc/cpuinfo might not be reliable. Use with
  caution.)
    cpu cores : 8
    siblings  : 8
    physical 0: cores 0 1 2 3 4 5 6 7
    physical 1: cores 0 1 2 3 4 5 6 7
  cache size : 20480 KB

From /proc/meminfo
MemTotal:      99010156 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

/usr/bin/lsb_release -d
  Red Hat Enterprise Linux Server release 6.5 (Santiago)

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
Linux localhost.localdomain 2.6.32-431.el6.x86_64 #1 SMP Sun Nov 10 22:19:54
EST 2013 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Mar 31 01:27

SPEC is set to: /spec
  Filesystem                                Type
  Size Used Avail Use% Mounted on
  /dev/mapper/ddf1_4c534920202020201000006019e5d2034711471157d3ceb3p2 ext4
  260G  68G  179G  28% /

Additional information from dmidecode:
  BIOS Insyde Corp. RMIBV365 09/06/2013
  Memory:
    12x Micron 36JSF1G72PZ-1G6K1 8 GB 1600 MHz 2 rank

(End of data from sysinfo program)

```

General Notes

Environment variables set by runspec before the start of the run:

```

LD_LIBRARY_PATH = "/spec/libs/32:/spec/libs/64:/spec/sh"
OMP_NUM_THREADS = "16"

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei	SPECfp2006 =	72.5
Huawei Tecal RH2285H V2	SPECfp_base2006 =	67.9

CPU2006 license: 3175	Test date: Mar-2014
Test sponsor: Huawei	Hardware Availability: Jan-2014
Tested by: Huawei	Software Availability: Nov-2013

General Notes (Continued)

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4
 Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
 runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>

The Huawei RH2285H v2 and Huawei RH2285 v2 models are electronically equivalent. The results have been measured on a Huawei RH2285H v2 model.

Base Compiler Invocation

C benchmarks:
 icc -m64

C++ benchmarks:
 icpc -m64

Fortran benchmarks:
 ifort -m64

Benchmarks using both Fortran and C:
 icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei	SPECfp2006 =	72.5
Huawei Tecal RH2285H V2	SPECfp_base2006 =	67.9

CPU2006 license: 3175	Test date: Mar-2014
Test sponsor: Huawei	Hardware Availability: Jan-2014
Tested by: Huawei	Software Availability: Nov-2013

Base Optimization Flags

C benchmarks:
 -xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

C++ benchmarks:
 -xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:
 -xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:
 -xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

Peak Compiler Invocation

C benchmarks:
 icc -m64

C++ benchmarks:
 icpc -m64

Fortran benchmarks:
 ifort -m64

Benchmarks using both Fortran and C:
 icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32
 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -unroll2 -ansi-alias
 -parallel

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei	SPECfp2006 =	72.5
Huawei Tecal RH2285H V2	SPECfp_base2006 =	67.9

CPU2006 license: 3175	Test date: Mar-2014
Test sponsor: Huawei	Hardware Availability: Jan-2014
Tested by: Huawei	Software Availability: Nov-2013

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
 -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -prof-use(pass 2) -unroll2
 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
 -no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
 -opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>
<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-V1.0-IVB-RevG.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>
<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-V1.0-IVB-RevG.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei	SPECfp2006 =	72.5
Huawei Tecal RH2285H V2	SPECfp_base2006 =	67.9

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2014
Hardware Availability: Jan-2014
Software Availability: Nov-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 23:28:44 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 22 April 2014.