



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECint®2006 = 60.0

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECint_base2006 = 57.1

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2014

Hardware Availability: Sep-2013

Software Availability: Oct-2013



Hardware

CPU Name: Intel Core i7-4960X
 CPU Characteristics: Intel Turbo Boost Technology up to 4.00 GHz
 CPU MHz: 3600
 FPU: Integrated
 CPU(s) enabled: 6 cores, 1 chip, 6 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 15 MB I+D on chip per chip
 Other Cache: None
 Memory: 16 GB (4 x 4 GB 2Rx4 PC3-14900U-13)
 Disk Subsystem: 480 GB Intel SSD 530 Series
 Other Hardware: None

Software

Operating System: Microsoft Windows 8.1 Pro 6.3.9600 N/A Build 9600
 Compiler: C/C++: Version 14.0.1.139 of Intel C++ Studio XE for Windows;
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 10.0 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECint2006 = 60.0

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECint_base2006 = 57.1

CPU2006 license: 13

Test date: Sep-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	285	34.2	278	35.1	278	35.1	219	44.6	219	44.6	218	44.7
401.bzip2	359	26.9	355	27.2	354	27.2	349	27.6	349	27.6	349	27.6
403.gcc	226	35.7	226	35.7	226	35.7	212	38.0	212	37.9	212	37.9
429.mcf	110	83.3	109	83.4	109	83.4	110	83.3	109	83.4	109	83.4
445.gobmk	339	30.9	339	30.9	339	30.9	324	32.4	324	32.4	324	32.4
456.hmmer	137	68.1	137	68.2	138	67.7	137	68.1	137	68.2	138	67.7
458.sjeng	376	32.1	377	32.1	377	32.1	376	32.1	377	32.1	377	32.1
462.libquantum	13.1	1580	13.1	1580	13.2	1570	13.1	1580	13.1	1580	13.2	1570
464.h264ref	342	64.8	342	64.8	342	64.8	293	75.6	293	75.6	293	75.6
471.omnetpp	200	31.3	200	31.3	199	31.4	185	33.8	185	33.8	184	33.9
473.astar	205	34.2	205	34.2	205	34.2	205	34.2	205	34.2	205	34.2
483.xalancbmk	121	57.1	121	57.2	121	57.2	121	57.1	121	57.2	121	57.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 14.0 was set up to generate 64-bit binaries with the command:

"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Platform Notes

```
Sysinfo program C:\SPEC14.0\Docs/sysinfo
$Rev: 6775 $ $Date::: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on Clt74D02B2C81C9 Fri Sep 12 10:21:26 2014
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name      : Microsoft Windows 8.1 Pro
OS Version   : 6.3.9600 N/A Build 9600
System Manufacturer: System manufacturer
System Model  : System Product Name
Processor(s) : 1 Processor(s) Installed.
[01]: Intel64 Family 6 Model 62 Stepping 4 GenuineIntel ~3601 Mhz
BIOS Version  : American Megatrends Inc. 4701, 5/7/2014
Total Physical Memory: 16,325 MB
```

```
Trying 'wmic cpu get /value'
DeviceID     : CPU0
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECint2006 = 60.0

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECint_base2006 = 57.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2014

Hardware Availability: Sep-2013

Software Availability: Oct-2013

Platform Notes (Continued)

```
L2CacheSize      : 256
L3CacheSize      : 15360
MaxClockSpeed   : 3601
Name             : Intel(R) Core(TM) i7-4960X CPU @ 3.60GHz
NumberOfCores    : 6
NumberOfLogicalProcessors: 12
```

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

```
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
                  -DSPEC_CPU_NO_NEED_VA_COPY
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hmmmer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption_cpp,--no_wchar_t_keyword
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint2006 = 60.0

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECint_base2006 = 57.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2014

Hardware Availability: Sep-2013

Software Availability: Oct-2013

Base Optimization Flags

C benchmarks:

```
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qauto-ilp32  
/F512000000
```

C++ benchmarks:

```
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
-Qauto-ilp32 /F512000000 shlw64M.lib  
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32  
/F512000000 shlw64M.lib  
-link /FORCE:MULTIPLE
```

```
401.bzip2: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qopt-prefetch -Qansi-alias -Qauto-ilp32  
/F512000000
```

```
403.gcc: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qauto-ilp32 /F512000000
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECint2006 = 60.0

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECint_base2006 = 57.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2014

Hardware Availability: Sep-2013

Software Availability: Oct-2013

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmr: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32
/F512000000

C++ benchmarks:

471.omnetpp: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000
shlw64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gnu: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-windows.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECint2006 = 60.0

ASUS P9X79 PRO motherboard (Intel Core i7-4960X)

SPECint_base2006 = 57.1

CPU2006 license: 13

Test date: Sep-2014

Test sponsor: Intel Corporation

Hardware Availability: Sep-2013

Tested by: Intel Corporation

Software Availability: Oct-2013

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Nov 5 10:22:54 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 4 November 2014.