



SPEC® CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp®_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Hardware

CPU Name: Intel Xeon E5-2643 v3
 CPU Characteristics: Intel Turbo Boost Technology up to 3.70 GHz
 CPU MHz: 3400
 FPU: Integrated
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 20 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (16 x 16 GB 2133 PC4-2133P-R)
 Disk Subsystem: 1 x 400 GB SAS SSD RAID 0
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)
 Kernel: 3.10.0-123.el7.x86_64
 Compiler: C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux; Fortran: Version 15.0.0.090 of Intel Fortran Studio XE for Linux
 Auto Parallel: No
 File System: ext4
 System State: Run level 3 (multi-user)
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Non-Compliant



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
416.gamess	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
433.milc	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
434.zeusmp	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
435.gromacs	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
436.cactusADM	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
437.leslie3d	24	NC	NC	NC	NC	NC	NC	12	NC	NC	NC	NC	NC	NC		
444.namd	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
447.dealII	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
450.soplex	24	NC	NC	NC	NC	NC	NC	12	NC	NC	NC	NC	NC	NC		
453.povray	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
454.calculix	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
459.GemsFDTD	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
465.tonto	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
470.lbm	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
481.wrf	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		
482.spm	24	NC	NC	NC	NC	NC	NC	24	NC	NC	NC	NC	NC	NC		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/transparent_hugepage/enabled
Filesystem page cache cleared with:
echo 1 > /proc/sys/vm/drop_caches
runspec command invoked through numactl, i.e.:
numactl --interleave=all runspec <etc>

Platform Notes

BIOS Configuration:

HP Power Profile set to Custom
HP Power Regulator to HP Static High Performance Mode
Minimum Processor Idle Power Core State set to C6 State
Minimum Processor Idle Power Package State set to No Package State
QPI Snoop Configuration set to Early Snoop
Thermal Configuration set to Maximum Cooling
Collaborative Power Control set to Disabled
Processor Power and Utilization Monitoring set to Disabled
Memory Double Refresh Rate set to 1x Refresh
Sysinfo program /cpu2006/config/sysinfo.rev6914
\$Rev: 6914 \$ \$Date: 2014-06-25 # \$ e3fbb8667b5a285932ceab81e28219e1
running on A-460cGen9-VP2 Mon Nov 10 04:36:14 2014

This section contains SUT (System Under Test) info as seen by various utilities. To remove or add to this section, see: <http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2643 v3 @ 3.40GHz
2 "physical id"s (chips)
24 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 6
siblings : 12
physical 0: cores 0 1 2 3 4 5

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp_rate2006 = **NC**

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Nov-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Platform Notes (Continued)

physical 1: cores 0 1 2 3 4 5
cache size : 20480 KB

From /proc/meminfo

MemTotal: 263845324 kB
HugePages_Total: 0
Hugepagesize: 2048 kB

From /etc/*release* /etc/*version*

os-release:
NAME="Red Hat Enterprise Linux Server"
VERSION="7.0 (Maipo)"
ID="rhel"
ID_LIKE="fedora"
VERSION_ID="7.0"
PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

uname -a:

Linux A-BL460c-Gen9-VP2 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57 EDT 2014 x86_64 x86_64 x86_64 GNU/Linux

dmidecode -s Nov 9 19:43

SPEC is set to: /cpu2006

Filesystem Type Size Used Avail Use% Mounted on
/dev/mapper/rhel-root ext4 310G 116G 179G 40% /

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HP I36 08/26/2014

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Platform Notes (Continued)

Memory:

16x HP 752369-081 16 GB 2 rank 2133

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/cpu2006/libs/32:/cpu2006/libs/64:/cpu2006/sh"

Binaries compiled on a system with Intel Core i5-4670K CPU + 16GB memory using RedHat EL 7.0

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icc -m64

Fortran benchmarks:

ifort -m64

Linker with Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64

416.gamess: -DSPEC_CPU_LP64

433.milc: -DSPEC_CPU_LP64

434.zeusmp: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Base Portability Flags (Continued)

```

435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

```

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

Fortran benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

Benchmarks using both Fortran and C:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3

```



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32 -L/opt/intel/composer_xe_2015/lib/ia32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
441.zeusmp: -DSPEC_CPU_LP64
435.gomacs: -DSPEC_CPU_LP64 -noFOR_main
436.cactusADM: -DSPEC_CPU_LP64 -noFOR_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deall: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -noFOR_main
459.GemstoneTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECfp_rate2006 = **NC**

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test date: Nov-2014

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2014

Tested by: Hewlett-Packard Company

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2)
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2)
-auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-mem-layout-trans=3
-unroll2

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2)
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2)
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2)
-opt-malloc-options=3

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2)
-opt-mem-layout-trans=3(pass 2) -prof-use(pass 2) -unroll14
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep-

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate2006 = **NC**

SPECfp_rate_base2006 = **NC**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll14
-auto -inline-cache -t-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2)
-opt-m-layers-trans=3(pass 2) -prof-use(pass 2)
-opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

450.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.xml>



SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c Gen9
(3.40 GHz, Intel Xeon E5-2643 v3)

SPECfp_rate2006 = NC

SPECfp_rate_base2006 = NC

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

Non-Compliant

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Nov 3 17:12:01 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 December 2014.