



SPEC® CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL380 Gen10

(2.50 GHz, Intel Xeon Platinum 8180)

SPECfp®2006 =

Not Run

SPECfp_base2006 =

146

CPU2006 license: 3


Test sponsor: HPE

Tested by: HPE

Test date: Jun-2017

Hardware Availability: Sep-2017

Software Availability: May-2017



Hardware

CPU Name: Intel Xeon Platinum 8180
 CPU Characteristics: Intel Turbo Boost Technology up to 3.80 GHz
 CPU MHz: 2500
 FPU: Integrated
 CPU(s) enabled: 28 cores, 1 chip, 28 cores/chip
 CPU(s) orderable: 1,2 chip(s)
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core

Software

Operating System: SUSE Linux Enterprise Server 12 (x86_64) SP2
 Kernel 4.4.21-68-default
 Compiler: C/C++: Version 17.0.4.196 of Intel C/C++ Compiler for Linux;
 Fortran: Version 17.0.4.196 of Intel Fortran Compiler for Linux
 Auto Parallel: Yes
 File System: btrfs
 System State: Run level 3 (multi-user)

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL380 Gen10

(2.50 GHz, Intel Xeon Platinum 8180)

SPECfp2006 =

Not Run

SPECfp_base2006 =

146

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date: Jun-2017

Hardware Availability: Sep-2017

Software Availability: May-2017

L3 Cache: 38.5 MB I+D on chip per chip
 Other Cache: None
 Memory: 96 GB (12 x 8 GB 2Rx8 PC4-2666V-R)
 Disk Subsystem: 1 x 450 GB SATA SSD, RAID 0
 Other Hardware: None

Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	21.1	645	21.3	639	<u>21.1</u>	<u>643</u>						
416.gamess	389	50.3	<u>388</u>	<u>50.4</u>	388	50.4						
433.milc	<u>97.6</u>	<u>94.1</u>	95.6	96.0	98.1	93.6						
434.zeusmp	23.9	380	<u>23.9</u>	<u>380</u>	24.0	380						
435.gromacs	132	54.1	132	54.1	<u>132</u>	<u>54.1</u>						
436.cactusADM	8.96	1330	<u>8.96</u>	<u>1330</u>	8.99	1330						
437.leslie3d	14.4	653	14.3	658	<u>14.3</u>	<u>657</u>						
444.namd	219	36.6	219	36.6	<u>219</u>	<u>36.6</u>						
447.dealII	<u>151</u>	<u>75.7</u>	150	76.0	152	75.2						
450.soplex	150	55.5	152	54.8	<u>151</u>	<u>55.4</u>						
453.povray	74.1	71.8	<u>74.1</u>	<u>71.8</u>	74.1	71.8						
454.calculix	109	75.5	<u>109</u>	<u>75.5</u>	109	75.5						
459.GemsFDTD	40.9	259	<u>40.9</u>	<u>259</u>	40.9	259						
465.tonto	180	54.6	<u>180</u>	<u>54.8</u>	179	55.0						
470.lbm	16.6	828	<u>16.4</u>	<u>839</u>	16.4	840						
481.wrf	76.5	146	76.8	145	<u>76.5</u>	<u>146</u>						
482.sphinx3	244	79.8	246	79.3	<u>244</u>	<u>79.8</u>						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"
 Transparent Huge Pages enabled by default.

Filesystem page cache cleared with:

shell invocation of 'sync; echo 3 > /proc/sys/vm/drop_caches' prior to run
 irqbalance service stopped using: "systemctl stop irqbalance.service"

Platform Notes

BIOS Configuration:

Hyper-Threading set to Disabled

Thermal Configuration set to Maximum Cooling

LLC Dead Line Allocation set to Disabled

XPT Prefetch set to Disabled

Workload Profile set to General Peak Frequency Compute

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL380 Gen10

(2.50 GHz, Intel Xeon Platinum 8180)

SPECfp2006 =

Not Run

SPECfp_base2006 =

146

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date:

Jun-2017

Hardware Availability: Sep-2017

Software Availability: May-2017

Platform Notes (Continued)

Energy/Performance Bias set to Maximum Performance
Sysinfo program /spec_cpu/cpu2006/config/sysinfo.rev6993
Revision 6993 of 2015-11-06 (b5e8d4b4eb51ed28d7f98696cbe290c1)
running on local Tue Jun 27 01:58:24 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) Platinum 8180 CPU @ 2.50GHz
        1 "physical id"s (chips)
        28 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 28
siblings : 28
physical 0: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 14 16 17 18 19 20 21 22 24
        25 26 27 28 29 30
cache size : 39424 KB
```

```
From /proc/meminfo
MemTotal:      98451040 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

```
/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 12 SP2
```

```
From /etc/*release* /etc/*version*
SuSE-release:
        SUSE Linux Enterprise Server 12 (x86_64)
VERSION = 12
PATCHLEVEL = 2
# This file is deprecated and will be removed in a future service pack or
release.
# Please check /etc/os-release for details about this release.
os-release:
        NAME="SLES"
VERSION="12-SP2"
VERSION_ID="12.2"
PRETTY_NAME="SUSE Linux Enterprise Server 12 SP2"
ID="sles"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:12:sp2"
```

```
uname -a:
Linux local 4.4.21-68-default #1 SMP Tue Oct 18 18:19:37 UTC 2016 (63cf368)
x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Jun 27 01:54
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL380 Gen10

(2.50 GHz, Intel Xeon Platinum 8180)

SPECfp2006 =

Not Run

SPECfp_base2006 =

146

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date:

Jun-2017

Hardware Availability: Sep-2017

Software Availability: May-2017

Platform Notes (Continued)

```
SPEC is set to: /spec_cpu/cpu2006
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sdb3        btrfs  445G   83G  359G  19%  /
```

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HPE U30 06/08/2017

Memory:

12x UNKNOWN NOT AVAILABLE

12x UNKNOWN NOT AVAILABLE 8 GB 2 rank 2666 MHz

(End of data from sysinfo program)

Regarding the sysinfo display about the memory installed, the correct amount of memory is 96 GB and the dmidecode description should have one line reading as:

12x UNKNOWN NOT AVAILABLE 8 GB 2 rank 2666 MHz

General Notes

Environment variables set by runspec before the start of the run:

KMP_AFFINITY = "granularity=fine,compact"

LD_LIBRARY_PATH = "/spec_cpu/cpu2006/lib/ia32:/spec_cpu/cpu2006/lib/intel64:/spec_cpu/cpu2006/sh10.2"

OMP_NUM_THREADS = "28"

Binaries compiled on a system with 2x Intel Xeon Platinum 8180 CPU + 384GB RAM memory using Redhat Enterprise Linux 7.3

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL380 Gen10

(2.50 GHz, Intel Xeon Platinum 8180)

SPECfp2006 =

Not Run

SPECfp_base2006 =

146

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date:

Jun-2017

Hardware Availability: Sep-2017

Software Availability: May-2017

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch
-ansi-alias -fp-model fast=2

```

C++ benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ansi-alias
-fp-model fast=2

```

Fortran benchmarks:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch
-fp-model fast=2

```

Benchmarks using both Fortran and C:

```

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -qopt-prefetch
-ansi-alias -fp-model fast=2

```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/HPE-Compiler-Flags-Intel-V1.2-HSW-revK.html>
<http://www.spec.org/cpu2006/flags/HPE-Platform-Flags-Intel-V1.2-SKX-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/HPE-Compiler-Flags-Intel-V1.2-HSW-revK.xml>
<http://www.spec.org/cpu2006/flags/HPE-Platform-Flags-Intel-V1.2-SKX-revB.xml>



SPEC CFP2006 Result

Copyright 2006-2017 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL380 Gen10

(2.50 GHz, Intel Xeon Platinum 8180)

SPECfp2006 =

Not Run

SPECfp_base2006 =

146

CPU2006 license: 3

Test sponsor: HPE

Tested by: HPE

Test date:

Jun-2017

Hardware Availability: Sep-2017

Software Availability: May-2017

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Fri Aug 11 13:23:27 2017 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 10 August 2017.