SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

IBM: RS/6000 7044-170
Zeus Technology Ltd.: Zeus 4.0r2

SPECweb99 = 1025

Test Date: Apr-2002
Tester: IBM

Hardware Avail:	Feb-2001	OS Avail:	Apr-2002	HTTP Software Avail:	Jan-2002	Sup. Software Avail:	Apr-2002	SPEC license #:	11

Hardware

Vendor:	IBM
Model:	RS/6000 7044-170
Processor:	450MHz POWER3-II
# Processors:	1 core, 1 chip, 1 core/chip
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	8MB(I+D) off chip
Other Cache:	None
Memory:	2 GB
Disk Subsystem:	15x18.2 SSA Disk(fast-write enabled)
Disk Controllers:	IBM SSA 160 SerialDisk Adapter
Other Hardware:	1 x Alteon ACESwitch 180

Software

Operating System:	AIX 5L V5.1
File System:	JFS
Other Software:	None

HTTP Software

Vendor:	Zeus Technology Ltd.
HTTP Software:	Zeus 4.0r2
API:	ISAPI
Server Cache:	FRCA (Fast Response Cache Accelerator)
Log Mode:	Binary CLF for Zeus, CLF for FRCA

Test Sponsor

Test Date:	Apr-2002
Tested By:	IBM
SPEC License:	11

Network

# of Controllers:	1
Network Controllers:	1 IBM Gigabit Ethernet-SX PCI Adapter
# of Nets:	1
Type of Nets:	Gigabit Ethernet
Network Speed:	1 Gb/sec
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	4
Model:	IBM eServer pSeries 640 Model B80
Processor:	375 MHz POWER3-II
# of Processors:	4
Memory:	4096MB
Network Controller:	1 Gigabit Ethernet-SX PCI Adapter
Operating System:	AIX 4.3.3
Compiler:	IBM VAC 5.0.1

Notes/Tuning Information

SUT Notes

APAR IY28102 was applied to AIX 5L V5.1
maxpgahead=32(the maximum number of pages to be read ahead,default=8)
minperm=5%(the point below which the page-stealer will steal file of computational pages,default=20%)
maxperm=95%(the point above which the page stealing algorithm steals only file page,default=80%)
1 transfer-log for requests processed by ZWS
1 frca-log for requests processed by FRCA
Disk layout: 1 disk for OS, 1 disk for webserver, 12 disks striped for file_set, 1 disk for web logfile
Set Gigabit Ethernet driver attribute copy_bytes=256 (copy packet into contiguous buffer on transmit if this many or less bytes, defult=2048)
"Set Gigabit Ethernet driver attribute slih_hog=100 (Interrupt events processed per interrupt, default=10)
"Set Gigabit Ethernet driver attribute tx_que_size=2048 (Software transmit queue size, default=8192)
frcactrl pctonintr 100 (frca set to allow 100% cpu time on interrupt, default=90)
frcactrl revaltimeout 100000 (set frca revalidation timeout to 100,000 seconds, default=300 seconds)
no(network option) tuning:
no -o tcp_sendspace=65536(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)
no -o send_file duration=100000(cached send_file expiration time, default=300)
no -o somaxconn=10240(max listen backlog, default=1024)
no -o nbc_max_cache=71680(max file size for network buffer cache, default=1048576)
no -o nbc_pseg=300000(max file entries in private segment,default=0)
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds, default=1)
no -o tcp_newreno=0 (disables the modification to TCP's Fast Recovery algorithm as described in RFC 2582, default=1)

HTTP API Notes

Zeus PEPP-06 SPECweb99 toolkit used for dynamic content
Compiled with IBM VAC 5.0.1
post.log in /weblog directory instead of doc_root
./Configure --sendfile=no --locking=semop

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Client Notes

APAR IY17356 was applied to AIX 4.3.3
no (network option) tuning:
no -o delayack=3(delay ack for connection setup and shutdown,default=0)
no -o delayackports={80}(delay ack ports,default={})
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds,default=1)
no -o tcp_sendspace=65536(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)

Other Notes

Starts 1 instance of Zeus
Zeus 4.0r2 global.cfg
tuning!bind_any no
tuning!cache_files 50001
tuning!cache_large_file 1048576
tuning!cache_small_file 4096
tuning!cache_stat_expire 180000
tuning!cache_flush_interval 180000
tuning!cache_max_bytes 0
tuning!num_children 3
tuning!keepalive yes
tuning!keepalive_timeout 1000
tuning!keepalive_max -1
tuning!listen_queue_size 9216
tuning!cbuff_size 65536
tuning!multiple_accept yes
tuning!sendfile yes
tuning!sendfile_maxsize 102400
tuning!sendfile_minsize 100
tuning!sendfile_reservefd 31991
tuning!so_nagle_off no
tuning!so_rbuff_size 32768
tuning!softservers no
tuning!unique_bind yes
tuning!use_poll no
tuning!cache_cooling_time 0
tuning!modules!cgi!cleansize 0
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!accelerator!frca!enabled yes
tuning!accelerator!frca!log!enabled yes
tuning!accelerator!frca!log!filename /weblog/log/frca-log
tuning!accelerator!frca!log!format CLF
tuning!accelerator!frca!maxsize 102400
tuning!accelerator!frca!minsize 100
Zeus_Site_Configuration:
modules!cgi!enabled yes
modules!isapi!enabled yes
bindaddr ip_addr, ip_addr, ip_addr
Tuning Disclosure: IBM-20011019.txt

Dynamic API: IBM-20011019_2-API.tar.gz