SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Sun Microsystems: Sun Fire V480
Zeus Technology Ltd.: Zeus 4.1

SPECweb99 = 4500

Test Date: Jun-2002
Tester: Sun Microsystems

Hardware Avail:	Jun-2002	OS Avail:	Mar-2002	HTTP Software Avail:	Feb-2002	Sup. Software Avail:	--	SPEC license #:	6

Hardware

Vendor:	Sun Microsystems
Model:	Sun Fire V480
Processor:	900MHz UltraSPARC III Cu
# Processors:	4 cores, 4 chips, 1 core/chip
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	8MB(I+D) off chip
Other Cache:	none
Memory:	32GB
Disk Subsystem:	1 x 36GB FC-AL 9 x 73GB Sun StorEdge T3
Disk Controllers:	Integrated FC-AL PCI Single FC Network Adapter
Other Hardware:	2 x Asante IntraCore 65120 Copper Switch

Software

Operating System:	Solaris 8 2/02
File System:	UFS
Other Software:	none

HTTP Software

Vendor:	Zeus Technology Ltd.
HTTP Software:	Zeus 4.1
API:	Zeus PEPP 0.6 ISAPI
Server Cache:	SNCA
Log Mode:	SNCA binary CLF

Test Sponsor

Test Date:	Jun-2002
Tested By:	Sun Microsystems
SPEC License:	6

Network

# of Controllers:	4
Network Controllers:	3 x SUN Gigabit Ethernet and 1 x Onboard Sun GigaSwift Ethernet
# of Nets:	4
Type of Nets:	Gigabit Ethernet
Network Speed:	1 Gb/s
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	16
Model:	Ultra 60
Processor:	450MHz UltraSPARC II
# of Processors:	2
Memory:	512MB
Network Controller:	Sun GigaSwift Ethernet
Operating System:	Solaris 8 2/02
Compiler:	Sun WorkShop 6 update 2 C 5.3

Notes/Tuning Information

SUT Notes

Operating System Notes

```
set autoup=60
set pcisch:pci_stream_buf_enable=0
set segmap_percent=80
set rlim_fd_max=262144
set rlim_fd_cur=262144
set maxpgio=128
set tcp:tcp_conn_hash_size=65536
set ge:ge_intr_mode=1
set ge:ge_dmaburst_mode=1
set ge:ge_tx_fastdvma_min=95
set ge:ge_nos_tmds=8192
set ge:ge_nos_txdvma=8192
set ge:ge_tx_bcopy_max=96
set ge:ge_pci_intr_blank_time=12
set ce:ce_bcopy_thresh=256
set ce:ce_dvma_thresh=256
set ce:ce_taskq_disable = 1
set ce:ce_ring_size = 256
set ce:ce_comp_ring_size = 1024
set ce:ce_tx_ring_size = 4096
set nca:nca_ppmax=3150000
set nca:nca_vpmax=3150000
```

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

set nca:nca_conn_hash_size=393209
set nca:nca_conn_req_max_q=10240
set nca:nca_conn_req_max_q0=10240
set nca:ncaurihash_sz=289669
set nca:ncavnodehash_sz=289669
set nca:nca_ppthresh=128
/usr/sbin/ndd -set /dev/ce rx_intr_time 32
/usr/sbin/ndd -set /dev/nca nca_max_cache_size 1000000
/usr/sbin/ndd -set /dev/nca nca_http_keep_alive_timeout 30000
/usr/sbin/ndd -set /dev/nca nca_use_segmap 1
/platform/sun4u/kernel/drv/ce.conf: interrupts=1;
/etc/nca/nca.if: ge0 ge1 ge2 ce1, /etc/nca/ncakmod.conf: status=enabled
/etc/nca/ncalogd.conf: status=enabled, logd_file_size=1000000000
/etc/nca/ncalogd.conf: logd_path_name=/http_logs/log0 ... /http_logs/log15
Mount /docs for file_set with noatime option - no inode access time updating

HTTP Software Notes

Zeus 4.1 Tuning
Enabled Modules - runningsites/wstest:
cgi, get, index, isapi, map, mime
Parameters - global.cfg:
tuning!modules!stats!enabled no
tuning!accelerator!nca!enabled yes
tuning!cache_files 199999
tuning!cache_max_bytes 0
tuning!cache_small_file 4096
tuning!cache_large_file 1048576
tuning!cache_stat_expire 31536000
tuning!cache_flush_interval 31536000
tuning!cache_cooling_time 0
tuning!sendfile yes
tuning!listen_queue_size 8192
tuning!so_wbuff_size 1048576
tuning!so_rbuff_size 0
tuning!modules!cgi!cleansize 0
tuning!cbuff_size 65536
tuning!sendfile_minsize 1
tuning!sendfile_reservefd 200000
tuning!bind_any no
tuning!keepalive no
For a description of Zeus tuning parameters, refer to http://support.zeus.com/faq/zws/v4/entries/settings.html

HTTP API Notes

Zeus PEPP 0.6 ISAPI used for dynamic content
Compiled with Sun WorkShop 6 update 2 C 5.3
./Configure --sendfile=no --locking=semop
CFLAGS: -I$INCLUDES -xtarget=ultra2 -Kpic -dalign -fns -fsimple=2 -ftrap=%none -xlibmil -xO5 -DCHECK_CONFIG
LDFLAGS: -z muldefs -G

Hardware Notes

Disk Configuration:
OS - 1 Internal FC-AL disk
file_set & post log - T3, 4 disk RAID 0 LUN
access log - T3, 4 disk RAID 0 LUN
Default rd_ahead on and cache auto set in T3

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Network Notes

3x4 load generators used 3 GE interfaces
1x4 load generators used 1 CE onboard interface

Client Notes

set sq_max_size=0, set hires_tick=1
ndd -set /dev/tcp tcp_smallest_anon_port 2048
ndd -set /dev/tcp tcp_time_wait_interval 60000
Client code generated with: CLFAGS=-xO4 -xchip=ultra -xarch=v8plusa
./configure --enable-posix-threads --enable-gethostbyname_r --enable-pthread_scope_system --enable-rlimit --enable-safe-usleep=no

Other Notes

Tuning Disclosure: Sun-20020610.txt
Dynamic API: SUN-20010402-API.tar.gz