SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Hewlett-Packard: HP NetServer LT6000
Microsoft: Internet Information Server 5.0

SPECweb99 = 1155

Test Date: May-2000
Tester: Hewlett-Packard Company

Hardware Avail:	May-2000	OS Avail:	Feb-2000	HTTP Software Avail:	Feb-2000	Sup. Software Avail:	Feb-2000	SPEC license #:	3

Hardware

Vendor:	Hewlett-Packard
Model:	HP NetServer LT6000
Processor:	700 MHz Xeon
# Processors:	2 cores, 2 chips, 1 core/chip
Primary Cache:	16KBI+16KBD on chip
Secondary Cache:	2MB on chip
Other Cache:	None
Memory:	4 GB
Disk Subsystem:	1 CDRW, 7 9GB 10K RPM
Disk Controllers:	1 IDE, 1 Integrated HP Netraid
Other Hardware:	None

Software

Operating System:	Windows 2000 Advanced Server
File System:	NTFS
Other Software:	None

HTTP Software

Vendor:	Microsoft
HTTP Software:	Internet Information Server 5.0
API:	ISAPI
Server Cache:	See Notes
Log Mode:	W3C Extended Log File

Test Sponsor

Test Date:	May-2000
Tested By:	Hewlett-Packard Company
SPEC License:	3

Network

# of Controllers:	1
Network Controllers:	Alteon Gigabit
# of Nets:	1
Type of Nets:	Gigabit Ethernet
Network Speed:	1Gb/sec
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	8
Model:	HP NetServer LPR
Processor:	"550 MHz Pentium II
# of Processors:	2
Memory:	256MB
Network Controller:	Alteon
Operating System:	"Windows 2000
Compiler:	Microsoft C++ Version 6

Notes/Tuning Information

SUT Notes

IIS settings: maximum performance.
IIS Home Directory: Access for Read & Write, Scripts & Executables.
IIS Virtual Directory spec99 points back to web server root, low application protection.
IIS Logging: W3C Extended logging, defaults plus bytes sent.

Operating System Notes

Tuning parameters:
TCP/IP Settings in registry:
- Tcpip/Parameters/MaxHashTableSize=0x10000, sets TCB hash table size to 8,192 entries, default is 512.
- Tcpip/Parameters/TcpTimedWaitDelay=0x3c, sets TIME_WAIT parameter to 60 seconds (non-RFC 1122), default is 240.
- Tcpip/Parameters/MaxFreeTwTcbs=400000, sets maximum number of TIME_WAIT tcbs to 400000.
- Tcpip/Parameters/MaxUserPort = 0xfffe, sets maximum open ports to 65534.
- Tcpip/Parameters/TcpWindowSize = 17520, sets TCP send/receive window size, default 8192.
- Tcpip/Parameters/NumTcbTablePartitions = 16, sets number of independent TCB table segments, default 4.

IIS Settings in Registry:
- Inetinfo/Parameters/ObjectCacheTTL=0xfffff, sets IIS object cache timeout in seconds, default 10 minutes.
- Inetinfo/Parameters/ListenBacklog=1000, default 25.
- Inetinfo/Parameters/AcceptExTimeout=1,sets time for accept ex socket to wait for receive, default 120.
- Inetinfo/Parameters/MaxPoolThreads=20,maximum network request threads per processor, default 10.
- Inetinfo/Parameters/LogFileFlushInterval=60, forces flush every 60 seconds, default 300.

Alteon NIC settings in registry:
- StatTicks=0, default 100000.

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

- SendCoalTicks=10000, sets number of microsec before send buffers are returned to host, default 100000.
- RecvCoalTicks=10000, sets number of microsec before recv buffers are given to host, default 100000.
- RecvCoalMax=80, sets number of frames received before notifying host, default 20.
- RxFlowControl=0 (off), default 1.

HTTP API Notes

Microsoft ISAPI for IIS 5.0 compiled with VC++ 6.0, code optimization = Pentium Pro.

Hardware Notes

One 9GB 10KRPM disk for OS, one for paging, and 5 striped for web pages.