SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

IBM: IBM eServer xSeries 370
Red Hat: TUX 2.0

SPECweb99 = 2700

Test Date: Feb-2001
Tester: IBM

Hardware Avail:	Mar-2001	OS Avail:	Feb-2001	HTTP Software Avail:	Feb-2001	Sup. Software Avail:	Feb-2001	SPEC license #:	11

Hardware

Vendor:	IBM
Model:	IBM eServer xSeries 370
Processor:	900 MHz Pentium III Xeon
# Processors:	1 core, 1 chip, 1 core/chip
Primary Cache:	16KBI+16KBD on chip
Secondary Cache:	2MB
Other Cache:	none
Memory:	8GB
Disk Subsystem:	5 X 18GB (IBM 19K1638)
Disk Controllers:	Onboard Adaptec
Other Hardware:	3 X ALTEON ACEswitch 180 GbE Switch

Software

Operating System:	RedHat Linux 7.0 with Threaded Web Server Add-On
File System:	ext2
Other Software:	None

HTTP Software

Vendor:	Red Hat
HTTP Software:	TUX 2.0
API:	TUX user API
Server Cache:	none
Log Mode:	Binary CLF

Test Sponsor

Test Date:	Feb-2001
Tested By:	IBM
SPEC License:	11

Network

# of Controllers:	3
Network Controllers:	Alteon ACEnic PCI
# of Nets:	3
Type of Nets:	Gigabit Ethernet
Network Speed:	1Gb/s
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	15
Model:	Intellistation Z Pro
Processor:	450Mhz Pentium II Xeon
# of Processors:	2
Memory:	256MB
Network Controller:	Alteon ACEnic PCI
Operating System:	Windows 2000 Professional
Compiler:	Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

1 disk for OS
3 disk software RAID0, using 2MB chunk size, for web pages
1 disk for logs

Operating System Notes

Tuning parameters:
- net.ipv4.ip_forward=1, default 0
- net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
- net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
- net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
- net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
- net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
- net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
- net.core.wmem_default = 10000000, default send socket buffer size, default 65535
- net.core.optmem_max = 10000000, default 10240
- net.core.hot_list_length = 10000, maximum number of skb-heads to be cached, default 128
- net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
- net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
- net.ipv4.ip_nonlocal_bind = 1, allow nonlocal IP addresses, default 0

Alteon NIC settings in /usr/src/linux/drivers/net/acenic.c
- tx_coal_tick = 300, default 400
- rx_coal_tick = 300, default 120
- max_tx_desc = 64, default 32
- max_rx_desc = 32, default 16

See config file for kernel build information

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP Software Notes

TUX Configuration
- net.tux.threads = 1, sets number of TUX threads, default 2
- net.tux.logging = 1, turns on logging, default 0
- net.tux.mode_allowed = 255, allowed file-permission bits, default 00004
- net.tux.mode_forbidden = 2, forbidden file-permission bits, default 00000
- net.tux.max_cached_filesize = 100000000, maximum size of cached object, default 100000
- net.tux.serverport = 80

HTTP API Notes

Tux API from Compaq-20010122-DL320-API.tar.gz