SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

IBM: IBM eServer pSeries 640 Model B80
Zeus Technology Ltd.: Zeus 4.0

SPECweb99 = 3569

Test Date: Oct-2001
Tester: IBM

Hardware Avail:	Oct-2001	OS Avail:	Dec-2001	HTTP Software Avail:	Oct-2001	Sup. Software Avail:	Dec-2001	SPEC license #:	11

Hardware

Vendor:	IBM
Model:	IBM eServer pSeries 640 Model B80
Processor:	450MHz POWER3-II
# Processors:	4 cores, 4 chips, 1 core/chip
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	8MB(I+D) off chip
Other Cache:	None
Memory:	16 GB
Disk Subsystem:	7x18.2 SSA Disk(fast-write enabled)
Disk Controllers:	IBM SSA 160 SerialRAID Adapter
Other Hardware:	4 x Alteon ACESwitch 180

Software

Operating System:	AIX 5L V5.1
File System:	JFS
Other Software:	None

HTTP Software

Vendor:	Zeus Technology Ltd.
HTTP Software:	Zeus 4.0
API:	ISAPI
Server Cache:	FRCA (Fast Response Cache Accelerator)
Log Mode:	Binary CLF for Zeus, CLF for FRCA

Test Sponsor

Test Date:	Oct-2001
Tested By:	IBM
SPEC License:	11

Network

# of Controllers:	4
Network Controllers:	4 IBM Gigabit Ethernet-SX PCI Adapter
# of Nets:	4
Type of Nets:	Gigabit Ethernet
Network Speed:	1 Gb/sec
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	12
Model:	RS/6000 44P-270
Processor:	375 MHz POWER3-II
# of Processors:	4
Memory:	2048MB
Network Controller:	1 IBM Gigabit Ethernet-SX PCI Adapter
Operating System:	AIX 4.3.3
Compiler:	IBM Cset++ Version 3.1.3

Notes/Tuning Information

SUT Notes

APAR IY22854 was applied to AIX 5L V5.1 to enable new hardware support
bindprocessor [process] [cpu] (Process affinity - bind 4 Zeus instances to 4 cpu's(1 instance to 1 cpu))
bindintcpu [interrupt level] [cpu] (Interrupt affinity - bind 4 Ethernet interrupts to 4 cpu's(1 interrupt to 1 cpu))
maxpgahead=32(the maximum number of pages to be read ahead,default=8)
maxfree=152(the number of frames on the free list at which page stealing is to stop,default=256)
minperm=5%(the point below which the page-stealer will steal file of computational pages,default=20%)
maxperm=95%(the point above which the page stealing algorithm steals only file page,default=80%)
Set Gigabit Ethernet driver attribute copy_bytes=256(copy packet into contiguous buffer on transmit if this many or less bytes, default=2048)
Set Gigabit Ethernet driver attribute large_send=yes(turn on large_send capability of TCPIP, default=no)
4 different logs for 4 zeus instances (1 log per zeus instance) for dynamic requests
frca-log.N (once the frca-log.N reaches 1GB, a new frca-log.N+1 is generated) for static requests
frcactrl pctonintr 100 (frca set to allow 100% cpu time on interrupt, default 90)
frcactrl revaltimeout 100000 (set frca revalidation timeout to 100,000 seconds, default=300 seconds)
Disk layout: 1 disk for OS, 1 disk for webserver, 4 disks for file_set, 1 disk for logfiles
no (network option) tuning:
no -o send_file duration=180000(cached send_file expiration time, default=300)
no -o somaxconn=9216(max listen backlog, default=1024)
no -o nbc_max_cache=100(max file size for network buffer cache,default=1048576)
no -o nbc_pseg=200000(max file entries in private segment,default=0)
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds, default=1)
no -o tcp_sendspace=65536 (default socket send buffer size, default=16384)
no -o tcp_recvspace=65536 (default socket receive buffer size, default=16384)

HTTP API Notes

Zeus PEPP version 0.6 SPECweb99 toolkit used for dynamic content
post.log in /weblog directory instead of doc_root
./Configure --sendfile=no --locking=semop

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Client Notes

APAR IY17356 was applied to AIX 4.3.3
no (network option) tuning:
no -o delayack=3(delay ack for connection setup and shutdown,default=0)
no -o delayackports={80}(delay ack ports,default={})
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds,default=1)

Other Notes

Starts 4 unique instances of Zeus sharing a common docroot
Each Zeus instance is bound to a unique IP address
Zeus 4.0 global.cfg(one per instance):
tuning!bind_any no
tuning!cache_files 100003
tuning!cache_large_file 9216
tuning!cache_small_file 9216
tuning!cache_stat_expire 180000
tuning!cache_flush_interval 180000
tuning!cache_max_bytes 0
tuning!num_children 1
tuning!keepalive yes
tuning!keepalive_timeout 1000
tuning!keepalive_max -1
tuning!listen_queue_size 9216
tuning!cbuff_size 1048576
tuning!multiple_accept yes
tuning!sendfile yes
tuning!sendfile_maxsize 1048576
tuning!sendfile_minsize 9216
tuning!sendfile_reservefd 32000
tuning!so_nagle_off no
tuning!so_rbuff_size 32768
tuning!softservers no
tuning!unique_bind yes
tuning!use_poll no
tuning!cache_cooling_time 0
tuning!modules!cgi!cleansize 0
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!accelerator!frca!enabled yes
tuning!accelerator!frca!log!enabled yes
tuning!accelerator!frca!log!filename /weblog/log/frca-log
tuning!accelerator!frca!log!format CLF
tuning!accelerator!frca!maxsize 1048576
tuning!accelerator!frca!minsize 100
Zeus_Site_Configuration:
modules!cgi!enabled yes
modules!isapi!enabled yes
Tuning Disclosure: IBM-20011019.txt
Dynamic API: IBM-20011019_2-API.tar.gz