

# SPECweb99\_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company: HP ProLiant BL30p  
Zeus Technology Limited: Zeus V4.2r4

SPECweb99\_SSL =1416

Test Date: May-2005  
Tester: Hewlett-Packard Company

Hardware Avail: Dec-2004 OS Avail: Aug-2004 HTTPS Software Avail: Nov-2003 Sup. Software Avail: Nov-2003 SPEC license #: 3

## Hardware

Vendor: Hewlett-Packard Company  
Model: HP ProLiant BL30p  
Processor: 3.2GHz Intel Xeon  
# Processors: 2 cores, 2 chips, 1 core/chip (Hyper-Threading enabled)  
Primary Cache: 12KBI+8KBD  
Secondary Cache: 512KB  
Other Cache: 2MB L3  
Memory: 4GB (2x2GB PC2100 DDR)  
Disk Subsystem: 2x60GB ATA100  
Disk Controllers: Integrated ATA  
Other Hardware: 2xHP BladeSystem Patch Panel

## Software

Operating System: SuSE Linux Enterprise Server 9  
File System: ext2  
Other Software: none

## HTTPS Software

Vendor: Zeus Technology Limited  
HTTPS Software: Zeus V4.2r4  
API: Zeus PEPP 0.9pre1 ISAPI for dynamic content  
Server Cache: none  
Log Mode: Binary Common Log Format

## Test Sponsor

Test Date: May-2005  
Tested By: Hewlett-Packard Company  
SPEC License: 3

## Network

# of Controllers: 2  
Network Controllers: Integrated NC7781  
# of Nets: 2  
Type of Nets: Gigabit Ethernet  
Network Speed: 1 Gb/s  
MSL (sec): 30 (Non RFC1122)  
Time-Wait (sec): 60 (Non RFC1122)  
MTU: 1500

## Clients

# of Clients: 4  
Model: HP ProLiant DL360 G3  
Processor: 3.06GHz 1MB L3 cache Intel Xeon  
# of Processors: 2 cores, 2 chips, 1 core/chip  
Memory: 512MB  
Network Controller: 2xIntegrated NC7781  
Operating System: Windows Server 2003 Std. Edition  
Compiler: Microsoft Visual C++ 6.0

## Notes/Tuning Information

### SUT Notes

1 drive used for OS and log, 1 drive used for workload  
1xHP BladeSystem p-Class enclosure  
1xHP BladeSystem p-Class Power Subsystem

### Operating System Notes

Filesystem mounted with noatime,nodiratime - no inode access time updating, no access control lists  
irq\_balancer disabled, default enabled  
Each NIC irq bound to two logical CPUs  
Each NIC's TX queue length set to 40000, default 100  
ulimit -n 72720, sets number of open files, default 1024  
/proc/sys/net/ipv4/conf/all/rp\_filter = 1 #enables source route verification, default 0  
/proc/sys/net/ipv4/tcp\_timestamps = 1 #turns TCP timestamp support off, default 1  
/proc/sys/net/ipv4/tcp\_max\_tw\_buckets = 2000000 #sets TCP time-wait buckets pool size, default 180000  
/proc/sys/net/ipv4/tcp\_rmem = 30000000 30000000 30000000 #maximum TCP read-buffer space allocatable, default 4096 87380 174760  
/proc/sys/net/ipv4/tcp\_wmem = 30000000 30000000 30000000 #maximum TCP write-buffer space allocatable, default 4096 16384 131072  
/proc/sys/net/ipv4/tcp\_mem = 30000000 30000000 30000000 #maximum TCP buffer space allocatable, default 31744 32256 32768  
/proc/sys/net/core/rmem\_max = 10000000 #maximum receive socket buffer size, default 65535  
/proc/sys/net/core/rmem\_default = 10000000 #default receive socket buffer size, default 65535  
/proc/sys/net/core/wmem\_max = 10000000 #maximum send socket buffer size, default 65535  
/proc/sys/net/core/wmem\_default = 10000000 #default send socket buffer size, default 65535  
/proc/sys/net/core/optmem\_max = 10000000 #default 10240  
/proc/sys/fs/file-max = 291879 #maximum number of open files, default 1024

### HTTPS Software Notes

tuning!unique\_bind yes  
tuning!cache\_cooling\_time 0  
tuning!cache\_files 282011

For more  
Information  
Contact

SPEC

info@spec.org  
http://www.spec.org

# SPECweb99\_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

## Notes/Tuning Information (Continued)

### HTTPS Software Notes (Continued)

tuning!cache\_flush\_interval 31536000  
tuning!cache\_max\_bytes 0  
tuning!cache\_stat\_expire 31536000  
tuning!cbuff\_size 65536  
tuning!clientfirst\_optimise yes  
tuning!keepalive yes  
tuning!keepalive\_max -1  
tuning!keepalive\_timeout 3600  
tuning!listen\_queue\_size 8192  
tuning!maxaccept 2500  
tuning!modules!cgi!cleansize 0  
tuning!sendfile yes  
tuning!sendfile\_maxsize 1  
tuning!so\_wbuff\_size 1048576  
tuning!softservers no  
tuning!ssl\_sessioncache\_size 7507  
tuning!modules!stats!enabled no  
See HP-20030414-tunings.txt for a description of the Zeus tuning parameters

### HTTP API Notes

Dynamic API: HP-20020724-API.tgz  
Zeus PEPP configured with the ./Configure --ssl=yes

### Client Notes

The alternative performance neutral alt.Win32 client was used.  
Tcpip\Parameters\MaxUserPort=0xffff, sets maximum open ports to 65534  
Tcpip\Parameters\TcpTimedWaitDelay=60, sets TIME\_WAIT parameter to 60 seconds (non-RFC 1122), default 240  
Tcpip\Parameters\MaxFreeTcb=100000, sets maximum number of TIME\_WAIT tcbs to 100,000  
Tcpip\Parameters\TcpWindowSize=65535, sets TCP receive window size, default 8192

### Other Notes

Server kernel: default SLES 9 (2.6.5-7.97-smp)