

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company: HP ProLiant BL45p
Zeus Technology Limited: Zeus V4.3r1 (64-bit)

SPECweb99_SSL =4752

Test Date: Sep-2005
Tester: Hewlett-Packard Company

Hardware Avail: Sep-2005 OS Avail: Jan-2005 HTTPS Software Avail: Nov-2003 Sup. Software Avail: Apr-2005 SPEC license #: 3

Hardware

Vendor: Hewlett-Packard Company
Model: HP ProLiant BL45p
Processor: AMD Opteron 854, 2.8GHz
Processors: 4 cores, 4 chips, 1 core/chip
Primary Cache: 64KBI+64KBD
Secondary Cache: 1MB on chip
Other Cache: none
Memory: 32GB (16x2GB PC3200 DDR)
Disk Subsystem: 2x72.8GB Ultra320 15Krpm
Disk Controllers: hp Smart Array 6i with 128MB BBWC
Other Hardware: hp BladeSystem RJ-45 Patch Panel 2

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP1
File System: ext2
Other Software: none

HTTPS Software

Vendor: Zeus Technology Limited
HTTPS Software: Zeus V4.3r1 (64-bit)
API: Zeus PEPP 0.9pre1 ISAPI for dynamic content
Server Cache: none
Log Mode: Binary Common Log Format

Test Sponsor

Test Date: Sep-2005
Tested By: Hewlett-Packard Company
SPEC License: 3

Network

of Controllers: 4
Network Controllers: 4xIntegrated NC7782
of Nets: 4
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 8
Model: HP ProLiant DL360 G3
Processor: 3.06GHz 1MB L3 cache Intel Xeon
of Processors: 2 cores, 2 chips, 1 core/chip
Memory: 2048MB
Network Controller: 2xIntegrated NC7781
Operating System: Windows Server 2003 Std. Edition
Compiler: Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

2xdrives RAID 0 used for OS, access log and workload
HP BladeSystem p-Class Enhanced Server Blade Enclosure
HP BladeSystem p-Class Power Subsystem

Operating System Notes

Filesystem mounted with noatime,nodiratime,noacl - no inode access time updating, no access control lists
irq_balancer daemon disabled, default enabled
One NIC irq bound per CPU, default round-robin
Each NIC's TX queue length set to 40000, default 100
ulimit -n 96201, sets number of open files, default 1024
1 > /proc/sys/net/ipv4/conf/all/rp_filter #enables source route verification, default 0
0 > /proc/sys/net/ipv4/tcp_timestamps #turns TCP timestamp support off, default 1
2000000 > /proc/sys/net/ipv4/tcp_max_tw_buckets #sets TCP time-wait buckets pool size, default 180000
30000000 30000000 30000000 > /proc/sys/net/ipv4/tcp_rmem #maximum TCP read-buffer space allocatable, default 4096 87380 174760
30000000 30000000 30000000 > /proc/sys/net/ipv4/tcp_wmem #maximum TCP write-buffer space allocatable, default 4096 16384 131072
30000000 30000000 30000000 > /proc/sys/net/ipv4/tcp_mem #maximum TCP buffer space allocatable, default 31744 32256 32768
10000000 > /proc/sys/net/core/rmem_max #maximum receive socket buffer size, default 65535
10000000 > /proc/sys/net/core/rmem_default #default receive socket buffer size, default 65535
10000000 > /proc/sys/net/core/wmem_max #maximum send socket buffer size, default 65535
10000000 > /proc/sys/net/core/wmem_default #default send socket buffer size, default 65535
10000000 > /proc/sys/net/core/optmem_max #default 10240
291879 > /proc/sys/fs/file-max #maximum number of open files, default 1024
TSO turned off for all NICs #default On

SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTPS Software Notes

tuning!bind_any no
tuning!unique_bind yes
tuning!cache_cooling_time 0
tuning!cache_files 384001
tuning!cache_flush_interval 316180000
tuning!cache_small_file 50000
tuning!cache_large_file 1048576
tuning!cache_max_bytes 24884901888
tuning!cache_stat_expire 316180000
tuning!cbuff_size 65536
tuning!clientfirst_optimise yes
tuning!keepalive yes
tuning!keepalive_max -1
tuning!keepalive_timeout 3600
tuning!listen_queue_size 16384
tuning!maxaccept 4048
tuning!modules!cgi!cleansize 0
tuning!sendfile no
tuning!sendfile_maxsize 0
tuning!sendfile_minsize 0
tuning!so_wbuff_size 1048576
tuning!softservers no
tuning!ssl_diskcache no
tuning!ssl_sessioncache_size 2617
tuning!ssl_cbuff_size 32840
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!num_children 4
tuning!num_cgid 4
See HP-20030414-tunings.txt for a description of the Zeus tuning parameters

HTTP API Notes

Dynamic API: HP-20020724-API.tgz
Zeus PEPP configured with the ./Configure --ssl=yes

Client Notes

The alternate performance neutral alt.Win32 client was used.
Tcipip\Parameters\MaxUserPort=0xffff, sets maximum open ports to 65534
Tcipip\Parameters\TcpTimedWaitDelay=60, sets TIME_WAIT parameter to 60 seconds (non-RFC 1122), default 240
Tcipip\Parameters\MaxFreeTwTcbs=100000, sets maximum number of TIME_WAIT tcbs to 100,000
Tcipip\Parameters\TcpWindowSize=65535, sets TCP receive window size, default 8192
Client 1, 2, 8 speed set to 100, Client 3, 4, 5, 6, 7 speed set to 110, default all clients equal

Other Notes

Server kernel: default SLES 9 SP1 (2.6.5-7.139-smp)