SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Advanced Micro Devices: MSI K7D Master/Athlon MP 2600+
Microsoft: IIS 5.0

SPECweb99 = 1770

Test Date: Jan-2003
Tester: Advanced Micro Devices

Hardware Avail:	Feb-2003	OS Avail:	Feb-2000	HTTP Software Avail:	Feb-2000	Sup. Software Avail:	Feb-2000	SPEC license #:	49

Hardware

Vendor:	Advanced Micro Devices
Model:	MSI K7D Master/Athlon MP 2600+
Processor:	Athlon MP 2600+, 2.13 GHz
# Processors:	2 cores, 2 chips, 1 core/chip
Primary Cache:	64KBI+64KBD on chip
Secondary Cache:	256KB
Other Cache:	none
Memory:	4 GB pc2100 DDR
Disk Subsystem:	3 18GB 15KRPM drives
Disk Controllers:	Compaq Smart Array 5312
Other Hardware:	1:Summit 7i, 1:Dell PowerConnect 5012

Software

Operating System:	Windows 2000 Advanced Server
File System:	NTFS
Other Software:	SP2

HTTP Software

Vendor:	Microsoft
HTTP Software:	IIS 5.0
API:	ISAPI
Server Cache:	None
Log Mode:	W3C Extended Log File Format

Test Sponsor

Test Date:	Jan-2003
Tested By:	Advanced Micro Devices
SPEC License:	49

Network

# of Controllers:	1
Network Controllers:	Intel Pro/1000XT
# of Nets:	1
Type of Nets:	Gigabit Ethernet
Network Speed:	1 Gb/s
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	8
Model:	Angstrom RenderFX Series 500
Processor:	AMD Athlon MP 2000+ 1.67 GHz
# of Processors:	1
Memory:	256MB
Network Controller:	Intel Pro 1000F
Operating System:	Windows 2000 Professional
Compiler:	Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

IIS settings: maximum performance.
IIS Home Directory: Access for Read & Write, Scripts & Executables.
IIS Virtual Directory spec99 points back to web server root, low app protection.

Operating System Notes

Tuning parameters:
TCPIP/Parameters/NumTcbTablePartitions= 32, sets number of independent TCB table segments, default 4.
TCPIP/Parameters/MaxFreeTwTcbs= 400000, sets maximum number of Time_Wait tcbs to 400,000.
TCPIP/Parameters/TcpTimedWaitDelay= 60, sets TIME_WAIT parameter to 60 seconds(non-RFC1122), default 240.
TCPIP/Parameters/MaxHashTableSize= 0x2710, sets TCB hash table size to 10000 entries, default 512.
TCPIP/Parameters/TCPWindowSize= 17520, sets TCP send/receive window size, default 8192.
TCPIP/Parameters/MaxUserPort= 0xfffe, sets maximum open ports to 65534.
NDIS/Parameters/ProcessorAffinityMask= 0, forces processor that handled interrupt to also handle that DPC, default any processor.
Inetinfo/Parameters/AcceptExTimeout= 1, sets time for accept ex socket to wait for receive, default 120.
Inetinfo/Parameters/LogFileFlushInterval= 60, forces flush every 60 seconds, default 300.
Inetinfo/Parameters/ListenBackLog= 1000, default 25.
Inetinfo/Parameters/MaxPoolThreads= 4, maximum network request threads per processor, default 10.
Inetinfo/Parameters/ObjectCacheTTL= 0xffffff, sets IIS object cache timeout, default 10 minutes.
Inetinfo/Parameters/PoolThreadLimit= 8, Max pool threads in system, default 2*#MB.
AFD/Parameters/TransmitWorker= 32, adjusts system default thread, default 16.
Control/FileSystem/NtfsDisableLastAccessUpdate= 1, prevents updating LastAccess time stamp on NTFS directories, default 0.
Control/SessionManager/MemoryManagement/IoPageLockLimit= 65536,increases I/O Pages limit to 64MB, default 512KB.
Intel nic registry settings:
NumTxDescriptors= 4096, Number of descriptors to send packets, default 256.
NumCoalesceBuffers= 768, Number of coalesce buffers for transmit acceleration, default 128.
ChecksumRxTcp= 1, offloads RX checksums to nic, default 0.
FlowControl= 0, Disables flow control default On (1).

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Operating System Notes (Continued)

TCPSegmentation= 1, enables TCP segmentation offload, default 0.

Hardware Notes

1 disk OS/logs, 2 disks RAID0 for web pages.

Other Notes

SUT requires an MSI K7D Master motherboard with BIOS version 1.5, an ATX 3hd capable case and an NSpire ps Model NSP-420P4B.Intfltr to bind nic irq to cpu0.
Dynamic API: Dell-19991214.zip