SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

IBM: pSeries 630 Model 6C4
Zeus Technology Ltd.: Zeus 4.2r1

SPECweb99 = 6895

Test Date: Feb-2003
Tester: IBM

Hardware Avail:	Feb-2003	OS Avail:	Nov-2002	HTTP Software Avail:	Mar-2003	Sup. Software Avail:	Mar-2003	SPEC license #:	11

Hardware

Vendor:	IBM
Model:	pSeries 630 Model 6C4
Processor:	1450MHz POWER4+
# Processors:	4 cores, 1 chip, 2 cores/chip, 1 chip/SCM
Primary Cache:	64KBI+32KBD (on chip) per core
Secondary Cache:	1536KB(I+D) unified (on chip) per chip
Other Cache:	8MB unified (off chip)/SCM, 2SCM in SUT
Memory:	32 GB
Disk Subsystem:	2x18.2GB(10KRPM) 16Bit SCSI Disk 16x18.2GB(10KRPM) SSA Disk (fast-write enabled)
Disk Controllers:	Wide/Ultra-2 SCSI I/O Controller IBM SSA 160 SerialRAID Adapter
Other Hardware:	4 x Alteon ACESwitch 180

Software

Operating System:	AIX 5L V5.2(64bit)
File System:	JFS2
Other Software:	None

HTTP Software

Vendor:	Zeus Technology Ltd.
HTTP Software:	Zeus 4.2r1
API:	ISAPI
Server Cache:	FRCA (Fast Response Cache Accelerator)
Log Mode:	Binary CLF for Zeus, CLF for FRCA

Test Sponsor

Test Date:	Feb-2003
Tested By:	IBM
SPEC License:	11

Network

# of Controllers:	4
Network Controllers:	4 IBM Gigabit Ethernet-SX PCI-X Adapter(14106802)
# of Nets:	4
Type of Nets:	Gigabit Ethernet
Network Speed:	1 Gb/sec
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	24
Model:	IBM eServer pSeries 640 Model B80
Processor:	375 MHz POWER3-II
# of Processors:	4
Memory:	4GB
Network Controller:	1 Gigabit Ethernet-SX PCI Adapter (14100401)
Operating System:	AIX 5.2
Compiler:	IBM Cset++ Version 5.1

Notes/Tuning Information

SUT Notes

APAR IY35693 was applied to AIX 5L V5.2
bindintcpu [interrupt level] [cpu] (Interrupt affinity - bind 4 Ethernet interrupts to 4 cpu's(1 interrupt to 1 cpu))
maxpgahead=64(the maximum number of pages to be read ahead,default=8)
minperm=5%(the point below which the page-stealer will steal file of computational pages,default=20%)
maxperm=95%(the point above which the page stealing algorithm steals only file page,default=80%)
4 different logs for 4 zeus instances (1 log per zeus instance) for dynamic requests
frca-log.N (once the frca-log.N reaches 1GB, a new frca-log.N+1 is generated) for static requests
Disk layout: 1 disk for OS, 1 disk for webserver, 14 disks striped for file_set, 2 disks web logfile)
Set Gigabit Ethernet driver attribute rxdesc_que_sz=512 (set RX descriptor queue size, default=1024)
Set Gigabit Ethernet driver attribute rxbuf_pool_sz=512 (set Receive buffer pool size, default=1024)
Set Gigabit Ethernet driver attribute copy_bytes=256 (copy packet into contiguous buffer on transmit if this many or less bytes, default=2048)
frcactrl pctonintr 100 (frca set to allow 100% cpu time on interrupt, default=90)
frcactrl revaltimeout 100000 (set frca revalidation timeout to 100,000 seconds, default=300 seconds)
no(network option) tuning:
no -o tcp_sendspace=65536(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)
no -o send_file duration=100000(cached send_file expiration time, default=300)
no -o somaxconn=10240(max listen backlog, default=1024)
no -o nbc_max_cache=40960(max file size for network buffer cache, default=1048576)
no -o nbc_pseg=800000(max file entries in private segment,default=0)
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds, default=1)
no -o tcp_newreno=0 (disables the modification to TCP's Fast Recovery algorithm as described in RFC 2582, default=1)
no -o tcp_inpcb_hashtab_siz=128021 (increase TCP PCB hash table size, default=24499)
SCM stands for Single Chip Module

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP API Notes

Zeus PEPP-06 SPECweb99 toolkit used for dynamic content
post.log in /weblog directory instead of doc_root
./Configure --sendfile=no --locking=semop
Compiled with IBM VAC 5.0.1
CFLAGS = -q64 -qlargetype -O2 -qmaxmem=8192
LDFLAGS = -q64 -qlargetype -bnoentry -Wl -G -bexpall -bM:SRE -lc -lbsd

Client Notes

no (network option) tuning:
no -o delayack=3(delay ack for connection setup and shutdown,default=0)
no -o delayackports={80}(delay ack ports,default={})
no -o tcp_timewait=5(ensure that TIME_WAIT is at least 60 seconds,default=1)
no -o tcp_sendspace=65536(default socket send buffer size, default=16384)
no -o tcp_recvspace=65536(default socket receive buffer size, default=16384)
AIX (thread-scheduling option) tuning:
AIXTHREAD_SCOPE=S (AIX pthread environment variable, set all threads have system based contention scope, {1:1}, default=P{8:1})
AIXTHREAD_SLPRATIO=1:1 (AIX pthread environment variable, controls the number of kernel threads that should be held in reserve for sleeping threads, default={12:1})
YIELDLOOPTIME=1000 (AIX pthread environment variable, controls the number of times to yield the processor before blocking on a busy lock, default=0)

Other Notes

Starts 4 unique instances of Zeus sharing a common docroot
Each Zeus instance bound to processor corresponding to its NIC
Zeus 4.2r1 global.cfg (one per instance)
tuning!bind_any no
tuning!cache_files 50021
tuning!cache_large_file 9216
tuning!cache_small_file 4096
tuning!cache_stat_expire 180000
tuning!cache_flush_interval 180000
tuning!cache_max_bytes 0
tuning!num_children 1
tuning!keepalive yes
tuning!keepalive_timeout 1000
tuning!keepalive_max -1
tuning!listen_queue_size 9216
tuning!cbuff_size 1048576
tuning!multiple_accept yes
tuning!sendfile yes
tuning!sendfile_maxsize 1048576
tuning!sendfile_minsize 100
tuning!sendfile_reservefd 31993
tuning!so_nagle_off no
tuning!so_rbuff_size 32768
tuning!softservers no
tuning!unique_bind yes
tuning!use_poll no
tuning!cache_cooling_time 0
tuning!modules!cgi!cleansize 0
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
tuning!accelerator!frca!enabled yes
tuning!accelerator!frca!log!enabled yes
tuning!accelerator!frca!log!filename /weblog/log/frca-log
tuning!accelerator!frca!log!format CLF
tuning!accelerator!frca!maxsize 1048576
tuning!accelerator!frca!minsize 100
Zeus_Site_Configuration (one per instance):
modules!cgi!enabled yes

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

Other Notes (Continued)

modules!isapi!enabled yes
bindaddr ip_addr1
Tuning Disclosure: IBM-20011019.txt
Dynamic API: IBM-20011019_2-API.tar.gz